

FORM 3 - PUBLISHED OPTION		RFB#2020-04 Ambulance and Transport Vehicles
Bidder Name:	Gen T, LLC	
Notes: (Important)	1) Use a single Form 3 for ALL Option/Accessory items and quote each on a single, separate line. DO NOT use multiple Form 3's... Add or insert additional lines as necessary. You may provide a pre-filled form. 2) Completely describe each item. Include the manufacturer's code or part number. 3) Options which replace standard equipment bid should be priced net of any credit due for the replaced item. 4) Options which are upgrades/downgrades of a bid item should be priced at the differential amount between the cost of the bid item and the upgrade/downgrade option.	

Code or Part No.	Option Description	Offered Price
CH-0001	TYPE 1: CHASSIS UPGRADE FORD F-SERIES FROM GAS TO DIESEL	10450
CH-0002	TYPE 1: CHASSIS UPGRADE FORD F-SERIES FROM 4X2 TO 4X4	4026
CH-0003	TYPE 1: CHASSIS UPGRADE FORD F-SERIES FROM F-350 to F-450 (on applicable models)	2045
CH-0004	TYPE 1: CHASSIS UPGRADE FORD F-SERIES FROM F-450 to F-550 (on applicable models)	1275
CH-0005	TYPE 1: CHASSIS UPGRADE TO LIQUID SPRINGS REAR SUSPENSION FORD F-SERIES / RAM 3500, 4500 & 5500 / CHEROLET C/K3500	12012
CH-0006	TYPE 1: CHASSIS UPGRADE RAM FROM 4X2 TO 4X4	3520
CH-0007	TYPE 1: CHASSIS UPGRADE RAM FROM 3500 to 4500 (on applicable models)	2545
CH-0008	TYPE 1: CHASSIS UPGRADE RAM FROM 4500 to 5500 (on applicable models)	1275
CH-0009	TYPE 1: CHASSIS UPGRADE CHEVROLET FROM 4X2 TO 4X4	3586
CH-0010	TYPE 1: CHASSIS UPGRADE CHEVROLET C-SERIES FROM GAS TO DIESEL	10450
CH-0011	TYPE 1: CHASSIS UPGRADE TO LIQUID SPRINGS FRONT SUSPENSION FORD F-SERIES / RAM 4500 & 5500	7986
CH-0012	TYPE 2: CHASSIS UPGRADE FORD TRANSIT TO ALL WHEEL DRIVE	5088
100030	Dri-Dek: Installed on exterior compartment floors only. Black	422
99-1053-B	Dri-Dek: Installed on exterior compartment shelves. Black- Add to all exterior compartment shelves as designated below. NOTE: Gen-T Models Only: a. Compt#2 – One shelf b. Compartment #3 – One shelf c. Compartment #6 – Three small shelves	495
99-1053-A	Dri-Dek: Installed on exterior compartment shelves. Black- Add to the exterior compartment shelves as designated below. NOTE: A Line units Only. a. Compt#2 – One shelf b. Compartment #3 – One shelf	389
100010	Flooring: Lonseal- LonCoin (Raised Circles) Specify Color:	594
100025	Flooring: Lonseal- LonPlate (Diamond Plate) Non-Standard Color Specify Color:	792
100020	Flooring: Lonseal- LonPlate (Diamond Plate) Specify Color:	594
100015	Flooring: Lonseal- LonRidge (Tic-Tac-Toe) Specify Color:	594
100040	Laminate: High Gloss Gray or White, must specify.	726
99-0449	Air Horns: Buell Air Horns- (1) Additional 3 Gallon Air Reservoir NOTE: Must order the Buell "Fast Recovery" compressor package. The supplemental reservoir is not compatible with the standard compressor.	297
99-1101	Air Horns: Buell Air Horns, "Fast Recovery System" P/N: 16122" ILOS air horn compressor system.	845
99-2288	Air Horns: Buell dual horns (1) 10" and (1) 12" to be mounted through the front bumper. There will be a momentary switch on the front console. A Buell "Fast Recovery System" air compressor to be mounted in compartment #2 with the tank mounted on the OEM chassis frame rail. NOTE: Type I Ford F-Series only	2607

99-2289	Air Horns: Buell dual horns (1) 10" and (1) 12" to be mounted through the front bumper. There will be a momentary switch on the front console. A Buell "Fast Recovery System" air compressor to be mounted in compartment #2 with the tank mounted on the OEM chassis frame rail. NOTE: Type III Chevy G-Series only	2607
99-2290	Air Horns: Buell dual horns (1) 10" and (1) 12" to be mounted through the front bumper. There will be a momentary switch on the front console. A Buell "Fast Recovery System" air compressor to be mounted in compartment #2 with the tank mounted on the OEM chassis frame rail. NOTE: Type III Ford E-Series only	2607
200011-F1	Air Horns: Buell dual horns through front bumper, momentary switch PN:MX09102 on front console, "Standard" compressor, tank, fittings. Make sure to order (1) 10" and (1) 12" airhorn. Specify Location Compressor: NOTE: Type I Ford F Series Only	2112
200015-F	Air Horns: Buell dual horns through front bumper, momentary switch PN:MX09102 on front console, "Standard" compressor, tank, fittings. Make sure to order (1) 10" and (1) 12" airhorn. Specify Location Compressor: NOTE: Type III Ford E Series Only	2112
200015-C	Air Horns: Buell dual horns through front bumper, momentary switch PN:MX09102 on front console, "Standard" compressor, tank, fittings. Make sure to order (1) 10" and (1) 12" airhorn. Specify Location Compressor: NOTE: Type III Chevy G Series Only	2112
99-1970	Back-Up System: RVS Audible Alert RVS-115W w/4 Sensors mounted on black powder coated sensor bracket PN: 33-10-5622 on rear bumper. Sensor brackets to install between the outer bumper pods and the rear dock bumper placing on sensor on each side of the dock bumper. Locate alert display on top of front console.	363
99-2260	Bumper: CPI cast aluminum rear bumper pods with Gen-T Logo- ILOS. Gen-T Models Only	350
99-0334-F3	Compartment #2: Drop Floor, 5" for Stair Chair storage PN: 33-10-4786 NOTE: For Type III Ford RP-90ES/MR, DB-147 and GT-154	264
99-0334-C1	Compartment #2: Drop Floor, 5" for Stair Chair storage PN: 33-10-4865 NOTE: For Type I Chevy GT-154	264
99-0334-F1	Compartment #2: Drop Floor, 5" for Stair Chair storage PN: 33-10-4865 NOTE: For Type I Ford GT-154	264
99-0334-C3	Compartment #2: Drop Floor, 5" for Stair Chair storage PN: 33-10-5604 NOTE: For Type III Chevy RP-90ES/MR and GT-154	264
99-0928	Compartment #2: Smooth Aluminum body, Open Storage, Double doors with gas strut hold-opens and offset in upper RH corner for (1) interior drawer and dual recessed suction configuration. Compartment Tub P/N: 33-103595. Sealed access to paddle handles in door panel. Stainless steel sill protector. NOTE: Install right hand door gas strut hold-open at bottom of offset in tub, this will be attached lower on the door panel. NOTE: Ford Chassis Gen-T 171 Type I Only (DELETE Adjustable aluminum shelf with DA finish)	330
99-0838	Compartment #2: Smooth Aluminum body, Open Storage, Double doors with gas strut hold-opens and offset in upper RH corner for (2) interior drawers configuration. Compartment Tub P/N: 33-10-2894. (1) Adjustable aluminum shelf with DA finish. Sealed access to paddle handles in door panel. Stainless steel sill protector. NOTE: Install right hand door gas strut hold-open at bottom of offset in tub, this will be attached lower on the door panel - reference unit 15-M089 if needed for picture. NOTE: Ford Chassis Gen-T 171 Type I Only	330
99-1169-E3	Compartment #2: SS center, smooth aluminum, floor th have 5-inch drop pan PN: 33-104786; Seat Belt retainer strap across mid-point of inboard wall anchored with footman loops in back corner of each side wall. NOTE: Ford RP-90 MR Type III.	264

99-2266	Compartment #2: Streetside middle, smooth aluminum body, Open Storage, Double doors with gas strut hold-opens. (1) Adjustable Gen-T aluminum shelf with DA finish with full perimeter lips. Sealed access to paddle handles in door panel, Stainless steel sill protector. Will have an offset for the action area pull out drawer. Order special tub PN# 77-113868. NOTE: GEN-T 171 Type I Model Only	360
99-2744	Divider: Compartment #2, full height fixed divider located 12" from the right hand wall. The area to the right side of the divider is for the storage of the waste container below the drop in waste opening in the action area countertop. NOTE: For Gen-T Only.	250
200050	Compartment #3: 24" wide Backboard Compartment on streetside rear. NO interior Stair Chair storage. (2) seat belt style straps in compartment. Smooth Aluminum body, ADP interior door panel. Gas Strut door hold-open, (1) LED light in ceiling. NOTE: RP-90ES Only.	990
200040	Compartment #3: 24" wide Backboard Compartment streetside rear. Shallow depth to provide room for interior stair chair storage. Install (2) seat belt style straps in Compartment #3 and (2) seat belt style straps in the stair chair pocket inside. Smooth aluminum body with ADP interior door panel, gas strut door hold-open and (1) LED light in ceiling. NOTE: RP-90ES Only.	990
99-0752	Compartment #3: Inside/Outside Access to Compartment #3 to have sliding polycarbonate doors ILOS 1/2" hinged Acrylic. NOTE: Gen-T 171 Models Only.	198
99-1860	Compartment #3: SS Rear Type III, 3/4 Height, Smooth Aluminum body, ADP interior door panel. DELETE Inside/Outside access, (1)- adjustable REDUCED DEPTH shelf with ADP finish in front of upper offset. Door with gas strut hold-open. NOTE: Offset tub to allow for interior 8" depth cabinet at upper inboard wall. See special tub print: 41-105662, see shelf print: 33-105889. NOTE: Type III 167 Ford Only.	330
99-2377	Compartment #3: SS Rear, 3/4 Height, smooth aluminum body. (NO Inside/Outside access). Door w/gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. This compartment will have an upper left corner offset for 22"W rear A/A shelf and 2nd offset at top inboard wall for shallow, interior cabinets. Both offsets to be same height. (2) narrow adjustable shelves PN: 75-113863 with full perimeter, upturned lips for Gen-T, to be located in offset area top of compartment. Order special tub PN# 77-113862. NOTE: GEN-T 171 Type I Model Only	600
99-2409	Compartment #3: SS Rear, 1/2 Height, smooth aluminum body, No adjustable shelf. Will have OUTSIDE ACCESS only. Door w/gas strut hold-open. Sealed access to paddle handle in door panel. Stainless steel sill protector. Will have a 7" drop floor for stair chair w/seat belt strap mounted to back wall and rear wall. NOTE: drop pan to be approximately 10"W x 30"L and installed aft of the shackle cover and as close to the right rear corner as physically possible. Drop Pan to be a part of and welded in bottom of compartment tub (P/N: 33-104025) before lining compartment. NOTE: Must choose interior cabinet configuration. Includes (1) adjustable shelf in this compartment. Lower Shelf Part #: 75-113853	462
99-0818	Compartment #3: SS Rear, 1/2 Height tub/door for 167 model-Tub PN: 41-103434. Smooth Aluminum body, ADP interior door panel. Door with gas strut hold-open. LED light. (If an adjustable shelf is required, add in additional option). NOTE: 167 Type III Models Only.	330
99-2746	Compartment #3 SS Rear: 3/4 Height, Smooth Aluminum body, w/extra tall 33" H Inside/Outside access, (2) narrow adjustable shelves w/DA finish and 1.5" lip on all four sides. Door w/gas strut hold-open. Sealed access to paddle handle in door panel. Stainless steel sill protector. NOTE: Requires new exterior tub for taller I/O Access, Tub #77-115174. NOTE: Inside/Outside Access to be 33.50"H x 24.00"W. NOTE: For Gen-T Only.	420
99-0789	Compartment #3: SS Rear, 1/2 Height, Smooth Aluminum body, DELETE STANDARD Inside/Outside access. Door with gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. NOTE: See special tub print: #33-10-0737 NOTE: Must choose interior cabinet configuration. NOTE: GT-171 Type III Only.	330

99-1363	Compartment #3: SS rear, 3/4 Height, Smooth Aluminum body, ADP interior door panel, SS Rear, with NO Inside/Outside Access, No shelf and offset for interior 2nd Action Area. See print 41-104586. NOTE: 154/167 Type III Only.	990
99-1560	Compartment #3: SS rear, 3/4 Height, Smooth Aluminum body. (DELETED Inside/Outside access). (1)-adjustable shelf with DA finish (NOTE: this shelf will be narrow width to fit between the offset wall in the tub, order shelf from print: 33-102474) Door with gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. NOTE: Offset in compartment for 22"W rear A/A shelf Only. See special tub print: 33-105140. NOTE: Gen-T 171 Type III Only.	330
99-1103	Compartment #3: Streetside rear 1/2 height on 171" body, Smooth Aluminum body, No adjustable shelf. Will have Outside access only. Door with gas strut hold-open. Sealed access to paddle handle in door panel. Stainless steel sill protector. Will have a 7" Drop Floor for Stair Chair with seat belt strap mounted to back wall and rear wall. NOTE: drop pan to be approximately 10"W x 30"L. Drop Pan to be a part of and welded in bottom of compartment tub (P/N: 33-104025) before lining compartment. NOTE: Gen-T Type I Only... Must choose interior cabinet configuration.	330
99-1039	Compartment #3: Streetside rear 3/4 height on 154" Body, Smooth Aluminum with Outside access only and (1) full width adjustable shelf. Door with gas strut hold-open. Will have offset at top inboard wall for shallow, interior cabinets (cabinets will be approximate 6" deep inside depth). Offset at top will reduce compartment depth to approximately 12" deep and the lower edge of the offset will be at the approximate height of the interior countertop area. See special tub print: 41-103902, See shelf print: 33-103904. NOTE: GT-154 Type III Only.	990
99-0713-T3	Compartment #3: Streetside rear 3/4 height on 171" body, Smooth Aluminum body with Inside/Outside access, (1)- adjustable shelf with DA finish (NOTE: this shelf will be narrow width to fit between the offset walls in the tub-see narrowed shelf print #33-102474). Door w/gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. NOTE: Offset in compartment for full length rear A/A shelf. See special tub print: #33-103731. NOTE: Make sure shelf is located at bottom of IS/OS access opening. NOTE: Gen-T Type III Only	198
99-0852-T3	Compartment #3: Streetside rear 3/4 height on 171" body, Smooth Aluminum body with DELETED Inside/Outside access. Door with gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. NOTE: Offset in compartment for 22"W rear A/A shelf and Offset at top inboard wall for shallow, interior cabinets. Both offsets to be same height. See special tub print: 33-103439 Rev A. (Delete the standard adjustable shelf, there is no shelf in this compartment). NOTE: Gen-T 171 Type III Only	330
99-0852-T1	Compartment #3: Streetside rear 3/4 height on 171" body, Smooth Aluminum body with deleted Inside/Outside access. (1)- adjustable shelf w/DA finish (NOTE: this shelf will be narrow width and shallower to fit between both of the offset walls in the tub, order shelf from print: 33-103012). Door w/gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. NOTE: Offset in compartment for 22"W rear A/A shelf and Offset at top inboard wall for shallow, interior cabinets. Both offsets to be same height. See special tub print: 33-103596. NOTE: Gen-T 171 Type I Only	660
99-0713-T1	Compartment #3: Streetside rear 3/4 height on 171" body, Smooth Aluminum body with Inside/Outside access, (1)- adjustable shelf with DA finish (NOTE: this shelf will be narrow width to fit between the offset walls in the tub, order shelf from print: 33-103012). Door with gas strut hold-open. Sealed access to paddle handle in door panel, Stainless steel sill protector. NOTE: Offset in compartment for full length rear A/A shelf. See special tub print: #33-105141. NOTE: Gen-T 171 Type I Only.	198
99-2569	Compartment #4/5: CS Forward, lower electrical storage area. Compartment to include a lower storage area for the on board electrical components designated within this work order. There will be an aluminum, louvered door with (2) twist latches for securing door to door frame. If inverter is to be located here, a separate option 99-1955 for a fan will need to be selected. NOTE: Gen-T models only.	294
200090	Compartment #6: Curbside rear spare tire aft of rear wheel well on RP90ES w/seat belt strap. Smooth Aluminum with rubberized urethane coating, drop floor for tire w/removable cover plate and (1) LED light in ceiling. NOTE: (no drop floor on Type I Chevy due to larger tire)	1617

99-2566	<p>Compartment #6: CS Rear, Smooth Aluminum body, Vertical backboard storage w/(2) seat belts restraints; (1) in upper Backboard section, (1) lower across Backboard and Stair Chair Section. Door w/gas strut hold-open. Sealed access to paddle handles in door panel, Stainless steel sill protector. Upper right section of compartment will have offset for protruding interior cabinetry. There will be a half height divider attached to bottom of the offset and run down to the floor. Order special tub PN #77-114444. Order divider PN #76-114449</p> <p>Note: See additional option in Cabinet Section for interior layout, required to use with this option.</p> <p>NOTE: Gen-T 171 Models Only.</p>	225
99-2127	<p>Compartment #7: Curbside rear smooth aluminum body. Open Storage, single access door with gas strut hold-open. Sealed access to paddle handles in door panel. (1) LED light in ceiling. Installed between CS rear wheelwell and compartment #6 IATS. Requires changing compartment #6 hold-open to a nylon strap.</p> <p>NOTE: GT-154 Models Only.</p>	1069
99-2126	<p>Compartment #7: Curbside rear smooth Aluminum body. Open Storage, Single access door with gas-strut hold-open. No shelf. Sealed access to paddle handles in door panel. (1) LED light in ceiling. Installed between CS rear wheelwell and compartment #6 IATS.</p> <p>NOTE: ME-167 Type III Only.</p>	1188
99-2125	<p>Compartment #7: Smooth Aluminum body, Open Storage, Single access door with 2" strap hold-open. No shelf. Sealed access to paddle handles in door panel. (1) LED light in ceiling. Installed between CS rear wheelwell and compartment #6 IATS.</p> <p>NOTE: Gen-T 171 Type III and Gen-T 158 Type I Only.</p>	1419
99-0740-C	Crawl Through: Chevy Type I crawl-through configuration between cab and module ILOS pass-through. (Does not include C/T door)	3630
99-0740-F	Crawl Through: Ford Type I crawl-through configuration between cab and module ILOS pass-through. (Does not include C/T door)	3630
99-1104	Divider: Backboard compartment, dividers to be coated with light gray rubberized urethane material same as compartment walls. Coating on (2) aluminum dividers ILOS smooth aluminum finish.	99
99-0389	Divider: Compartment #1, smooth aluminum, full height, vertical divider with DA finish fixed to rear wall. Locate O2 Cylinder towards the right hand wall in the compartment (not in the center) and the divider to the left of the cylinder bracket. Divider PN: 33-102938.	257
99-0938	<p>Divider: Hinged 50" high in Compartment #1, mounted to the left side of the O/2 tank. This divider will have a full length, stainless steel hinge attached to the rear wall to allow it to swing forward towards the cab to create additional room for changing the tank. There will be a spring loaded latch mounted on the divider bottom. See print: #33-103854, Latch is Austin P/N: AH 2695 SS.</p> <p>NOTE: Gen-T Models Only</p>	330
200110	Fender Flares: Black rubber, ILOS stainless steel on Gen-T II 171 only.	0
200130	Fender Flares: Roll formed stainless steel, ILOS rubber.	363
99-0046	Fuel Fill: Locking Cap on Fuel Fill	20
200150	Grab Handle: Exterior, Mounted on curbside wall aft of entry door. Use PN: 63-07-3200 (anti-slip grab handle).	132
99-2042	Grille Guard: Buckstop "Outback", Black Semi finish, NO winch option, NO openings for lights, WITH opening pre cut to receive Whelen SA315 outboard and dual Buell air horns on inboard side of bail bracket. Will have mounting tabs installed inside to accept SA315 mounting bracket.	4950
99-1476	<p>Grille Guard: Buckstop "Outback", Black Semi finish, NO winch option, NO openings for lights, WITH opening pre cut to receive Whelen SA315 on bail bracket and cross mounted support for mounting optional lighting above the shelf of the bumper. Have mounting tabs installed inside to accept bracket.</p> <p>NOTE: Ford F-450/550 Only</p>	4950
99-0361	Grille Guard: Chrome- Big Tex #77754 Installed on C/K 3500	1789
99-1175	Grille Guard: Chrome- GoRhino #3155MB Installed on G-3500	2482
99-1177	Grille Guard: Chrome- GoRhino #3373MC Installed on F-350/450	2515
99-1176	Grille Guard: Chrome- GoRhino with Step #3173MC Installed on C/K 3500	2548
99-1573	<p>Grille Guard: Ranch Hand Legend GGF171BL1, NO winch or camera cut-out option. Ford F-350/450 Models Only. NOTE: REQUIRES RELOCATING GRILLE LIGHTS TO THE GRILLE GUARD CENTER MESH AREA. USE LOOM FOR GRILLE LIGHT WIRES.</p> <p>NOTE: MOUNTING BRACKETS NEED ORDERED TO "SANDWICH" GRILLE LIGHTS ON GRILLE GUARD - PER PRINT 33-105640 x1 FOR EACH LIGHT</p>	1789

99-0117	IV Clip: Perko wall mount fender clip Location: Must provide mounting location	20
200160	IV Hanger: Cast Products PN:2008, flush mount, fold down, rubber, IATS Specify Location(s):	86
99-0423	Lights: Compartment, TecNiq Flexible LEDs: 9", 27", 36" 45", 54", ILOS compartment lights. Locate: Compartment #1- (1) 44" E44-W010V-1 Locate: Compartment #2- (2) 27" E44-W06V-1 Locate: Compartment #3- (2) 44" E44-W010V-1 Locate: Compartment #4- (1) 36" E44-W08V-1 Locate: Compartment #6- (2) 54" E44-W012V-1 Locate: Compartment #7- (1) 9" E44-W02V-1 (if ordered)	396
99-1294	Lights: Courtesy, (2) TecNiq EON E03-W000-1 LED lights mounted on vertical surface of running board on each side of the Type I chassis only, wired to OEM dome lights.	145
99-0283	Lights: Courtesy, (2) Whelen 2" TOCACCCR with TGROM2 rubber grommet, mounted on the front wall of the module above the running boards on each side of the chassis. Note: use on Type III modes only.	198
99-1121	Lights: Courtesy, (2) Whelen 3" 3SCOCDCR with 3GROMMET rubber grommet, mounted on the front wall of the module above the running boards on each side of the chassis. Note: To be used on Type III mods only.	238
99-0160	Mirrors: Velvac 20/20XG, Chrome Head Assembly Pair LH/RH #715953- ILOS	759
99-1184	Mirrors: Velvac 2020XG for 2015 E-350/450, Kit #716343, motorized, heated deluxe head with bottom convex, with lighted turn arrow in mirror, Black	1221
99-1004	Mirrors: Velvac 2020XG for 2015 E-350/450, Kit #716346, motorized, heated deluxe head with bottom convex, Lights on arms, Black	964
200215	Power Door Locks: (1) Compartment Door Only, wired to OEM system. (Does not include additional lock switches inside module)	231
200210	Power Door Locks: (2) Entry Doors Only, wired to OEM system. (Does not include additional lock switches inside module)	330
200200A	Power Door Locks: All Entry and Compartment Doors, wired to OEM door lock system.	1162
200200Gen-T	Power Door Locks: All Entry and Compartment Doors, wired to OEM door lock system. Includes (1) switch by Curbside Entry Door interior in standard 4-position switch panel and (1) at Rear Curbside Wall - Gen-T II ONLY	1162
200200C	Power Door Locks: Chevy Type I, All Entry and Compartment Doors, THIS WILL ONLY UNLOCK THE MODULE LOCKS, NOT CAB DOORS. (Does not include additional lock switches inside module) NOTE: See option 99-0404 in electrical for adding on lock switches at the entry doors	1162
99-0701	Power Door Locks: Key Pad, programmable for power door locks. Requires the selection of power door lock option for the module doors. NOTE: Ford Chassis Only PN: ES7Z-14A626-A	251
200220	Power Door Locks: Keypad Entry - Essex p/n: KE-1701BH Requires selection of Power Door option. Specify Location of Keypad:	429
200210A	Power Door Locks: Specify Entry Doors Only, wired to OEM system. Includes (1) switch by Curbside Entry Door interior in standard 4-position switch panel and (1) at Rear Curbside Wall - Gen-T ONLY Specify Location of Switch:	363
99-0678E	Power Door Locks: Stealth Switch on Ford, Power Door Lock System, Push Button Switch (Grille bracket on E-series: Ford 33-102402; no bracket required on F-series) LOCATION:	86
99-0678C	Power Door Locks: Stealth Switch, Chevy Type I Only, Power Door Lock System, Push Button Switch (Grille brackets: no bracket required on Chevy Cab/Chassis) NOTE: THIS WILL ONLY UNLOCK THE MODULE LOCKS, NOT CAB DOORS LOCATION:	86
99-0678G	Power Door Locks: Stealth Switch, Power Door Lock System, Push Button Switch (Grille brackets: Chevy G-Series 33-102397) LOCATION:	86
99-0678D	Power Door Locks: Stealth Switch, Power Door Lock System, Push Button Switch (Grille brackets: FOR DODGE CHASSIS - Bracket #33-105690 LOCATION: FRONT GRILLE AREA	86

99-2108	Power Door Locks: Stealth Switch, Power Door Lock System, Push Button Switch LOCATION: attached to aluminum plate at bottom of rear corner cap on streetside. See print for plate: 33-105600	86
99-0667	Rub Rails: Extruded rubber rub rails- ILOS	264
200277	Running Boards: "Starburst" Grip Punched, Chevy/GMC, Ford, Sprinter Type III	66
200260	Running Boards: Aluminum Diamond Plate, Type II GM	795
99-0539	Running Boards: Sprinter Chassis/Cab, Owens. PNs: OC8434X-01 with 10-1035 Brackets	634
99-1362	Seat Belt: Automotive Style strap with Buckle - (1) additional in exterior compartment. Location: Must Specify	66
99-0250-1	Shelf: (1) Adjustable shelf, smooth aluminum with lip, DA finish, forward of backboard divider in compartment #6. Gen-T ONLY Specify Location:	178
99-0250-2	Shelf: (2) Adjustable shelves, smooth aluminum with lip, DA finish, forward of backboard divider in compartment #6. Gen-T ONLY Specify Location:	277
99-0250-3	Shelf: (3) Adjustable shelves, smooth aluminum with lip, DA finish, forward of backboard divider in compartment #6. Gen-T ONLY Specify Location:	376
99-2745	Shelf: Adjustable for compartment #2. Install maximum width adjustable shelf between the right hand wall and the fixed divider (from option 99-2744). Shelf is for storage of the Rubbermaid waste container below the waste opening in the action area shelf. NOTE: For Gen-T Only.	250
99-0839	Shelf: Additional, adjustable smooth aluminum PN 33-103012 .125" with DA finish, exterior compartment #3 with offset for interior monitor storage shelf. Shelf is to mount in upper section of compartment for I/O access storage. NOTE: Gen-T 171 Type I Models Only	132
99-2520	Shelf: Custom, fixed "L" shaped shelf. .125" smooth aluminum w/ lips, DA finish, adjustable for backboard divider - Gen-T ONLY, See Print: 75-114140 Specify Location: compartment #1 at the top of the O2 Access Door, from right hand wall to center of compartment. Shelf will then turn 90 degrees and terminate at the compartment ceiling culminating as an "L" shape. Note: If hinged divider is selected below this shelf, provision shelf for slide lock catch for divider on bottom of shelf.	250
99-2522	Shelf: Adjustable, Smooth Aluminum w/ 4 lips, DA finish, Adjustable full width and depth. - Gen-T 171 models ONLY, See Print: 75-113954. Specify Location: compartment #1 above O2 tank.	150
99-2565	Shelf: (1) Adjustable shelf, DA finish, in #3 Compartment with 1" upturned lips on all 4 sides, full width and full depth of the #3 Compartment inside the adjustable shelf track. Note: Gen-T models only. Locate: in lower half of compartment	225
200280	Shelf: Adjustable, Aluminum Diamond Plate, Exterior Compartment Specify Location:	178
200280a	Shelf: Adjustable, Smooth Aluminum w/DA finish, Exterior Compartment - Gen-T ONLY Specify Location:	178
99-0551	Shelf: Aluminum PN 33-101766, adjustable .125" smooth with DA finish, with 6" outboard lip, 1" inboard lip for 3/4-Height Compartment #3 with IS-OS Access. NOTE: Gen-T models only	66
99-0609	Shelf: Aluminum PN 33-102104, fixed smooth aluminum w/lips for Compartment #1. NOTE: Gen-T 171 Models Only	178
99-1066	Shelf: Fixed/Removable- .125" aluminum w/DA finish, Exterior Compartment #2 - Type I 158 Gen-T ONLY; Short shelf mounted upper section of compartment will have lips bent upward on front and rear edges and sit on angle brackets at the sides, bolted; back left corner to have 45 taper for wires. All electrical components to fit above this shelf. See print: 33-105514	178
99-0007ADP	Splash Guard: ADP, below fuel fill (Fuel Fill Only) NOTE: Not for use on Diesel Chassis or below DEF fill	99
99-0007SS	Splash Guard: Stainless Steel Plate, installed below fuel fill and DEF fill NOTE: Must use Stainless Steel on Diesel Chassis	172

99-2465	Splash Shields: ADP, Equal Height to front Corner Guards PN: 33-104257, 20.1875" wide, 16.625" tall. Installed on front face of module, one per side, inboard of corner guards. Note: Gen-T only w/both front drop skirts.	120
99-0090	Stair Chair: ADP stair chair carrier, attach to the door liner on compartment #3 interior door panel w/seat belt strap to secure stair chair, print #: 33-101491	231
99-0886	Stair Chair: Rubberized urethane coated smooth aluminum stair chair carrier, attach to the door liner on compartment #3 interior door panel with seat belt strap to secure stair chair. PN: 33-10-3144	231
99-0791	Stone Guards: ADP, 30" High corner guards; and 30" High front wall guard installed from each corner guard and extending behind OEM cab, Type I only (Not to be used on Gen-T), ILOS; PN's 33-103286, 33-103287	198
99-0175	Stone Guards: ADP, Shaped to cab contour, installed between the corner ADP stone guards and the lower front of the body. PNs: 33-10-4256 & 33-10-4257 NOTE: Gen-T Type I Conversions Only	99
99-2217	Stone Guards: Fire Truck Quality rear kick panel below rear doors, C/S and S/S rear corner guards, C/S and S/S front corner guards and front wall splash guards extending behind the running boards and OEM cab.	450
99-2476	Stainless Steel Exterior Trim Package on GEN-T 171 models only: (2) rear corner guards 12.625" tall (PN: 33-106051), (2) front corner guards 16.625" tall (33-106052), (2) front splash shields 16.625" tall (PN: 33-114231), (1) rear kick plate (PN: 33-106050, and (1) rear step bumper guard (PN: 33-114195) to be brushed stainless steel ILOS.	300
200185-SV	Stainless Steel Exterior Trim Package on GEN-T 171 models only: (2) rear corner guards 12.625" tall (PN: 33-106051), (2) front corner guards 16.625" tall (33-106052), (2) front splash shields 16.625" tall (PN: 33-114231), (1) rear kick plate (PN: 33-106050, and (1) rear step bumper guard (PN: 33-114195) to be brushed stainless steel ILOS.	4290
200180-G	Tire Chains: On-Spot Chain System PN: 15-15-5000 for GM G-Series. Specify Mounting Location for Air Compressor:	4620
200190-E3	Tire Chains: On-Spot Chain System PN: 15-15-5001 for Ford E350 with 044421 mounting brackets. Specify Mounting Location for Air Compressor:	4785
200190-E4	Tire Chains: On-Spot Chain System PN: 15-15-5001 for Ford E450 with 044380-D OEM mounting brackets. Specify Mounting Location for Air Compressor:	4785
200185-S	Tire Chains: On-Spot Chain System PN: 15-15-5001 for MB Sprinter with 04-SP3A mounting brackets. Specify Mounting Location for Air Compressor:	4290
200190-F4	Tire Chains: On-Spot Chain System PN: 15-15-5002 for all Ford F-450 4x4 with 05-RS120 mounting brackets. Specify Mounting Location for Air Compressor:	4290
99-1776-GA	Tow Eyes: Frame-Mounted Through Rear Kick Plate, Chevy 94"W Cutaway. PNs: K2032WN, BC0013, rear wall & kickplate PN: 33-102008-C per chassis. NOTE: Chevy G3500/4500 GT-154 and GT-167 Models Only.	508
99-1776-C1	Tow Eyes: Frame-Mounted Through Rear Kick Plate, Chevy 94"W Type I Cab/Chassis. PNs: K2032, BC0013, 30-102286 NOTE: This requires a different rear kick panel PN: 33-102709 NOTE: Chevy C/K-3500 GT-154 Model Only.	508
99-1776-GM	Tow Eyes: Frame-Mounted Through Rear Kick Plate, Chevy 96"W Type III Cutaway. PNs: K2032WN, BC0013, rear wall & kickplate PN: 33-101759-C per chassis. NOTE: Chevy G4500 Gen-T 171 Only.	508
99-0545	Tow Eyes: FraGT-Mounted Through Rear Kick Plate, Ford E-350/450 94"W Type III Cutaway. PNs: K2032WN, BC0013 and PN: 33-10-5445 fraGT plate & 33-104618 kickplate prints per chassis. NOTE Ford E350/450 GT-154/GT-167 Models Only.	508
99-1776-EM	Tow Eyes: Frame-Mounted Through Rear Kick Plate, Ford E-450 96"W Cutaway. PNs: K2032WN, BC0013 and PN: 33-105445 frame plate and PN: 33-10-5446 kickplate per chassis. NOTE: Ford E-450 Gen-T 171 Model Only.	508
99-1776-FA	Tow Eyes: Frame-Mounted Through Rear Kick Plate, Ford F-350/450/550 94"W Type I Cab/Chassis. PNs: K2032WN, BC0013, rear wall & kickplate PN: 33-10-2709 prints per chassis. NOTE Ford F350/450/550 GT-154 Model Only.	508
99-1776-FM	Tow Eyes: Frame-Mounted Through Rear Kick Plate, Ford F-450 96"W Type I Cab/Chassis. PNs: K2032WN, BC0013 and PN: 33-10-3085 kickplate prints per chassis. NOTE Ford F450/550 Gen-T 158/171 Models Only.	508
200300	Undercoating: Per OEM Guidelines (Van Only)	165

99-1098	Windows: Privacy tint, dark vinyl applied to all three entry module entry door windows. NOTE: Module application only.	433
99-2184	Windows: Privacy tint, dark vinyl applied to all three entry module entry door windows. PER CALIFORNIA ORDERS - TINT TO BE 3% OVER NORMAL TINTED WINDOWS ON MODULE ENTRY DOORS - TO BE "3% GRADE". NOTE: Module application only.	433
99-0864	Windows: Privacy Tint, Dark vinyl applied to streetside sliding entry door and two rear entry doors, Transit Only	433
200320	Windows: Sliding window in entry door ILOS Fixed Specify Location(s):	86
99-0890	Windows: Type I pass-through, sliding polycarbonate window with extruded handle mounted to HDPE backer with track material.	462
99-0931	Lighting: Cabinet, (1) TecNiq D04-W001-1 Linear Dragon Light Vertical, White LED with white case (D04-0WV0-1) and 36" wire. Will have Rocker On/Off Switch in rear switch panel, labeled "Cabinet Lights" (MX09188) - operates all at same time. Price per light. Locate LEDs just inside front top corner of each cabinet. NOT ON BACK WALL. Run wires from entry point on the upper rear cabinet corners and along the upper cabinet corners to each LED. Loom the wires and attach with P-clamps. Cabinet Locations: Must Specify	66
300100	Lights: Brake and Turn, Interior, LED, Under rear overhead cabinet, Two (2) amber wired to turn signals; One (1) red wired to brake circuit.	66
99-0203	Lights: DOT Marker, (2) TecNiq LED S34-AA09-1 Amber marker lights, (1) each side of body at front corner extrusion. Wire to Turn Signal Circuit.	132
99-0812	Lights: DOT, Brake/Tail, Turn, Back Up: Whelen 900 Series Super LED 90BTT, 90A00TAR and 90CC5SCR with chrome flange, ILOS 700 Series (Package PNs: 60BTTC, 60A00TAR, 60C00VCR) LEDs	739
99-1489	Lights: DOT, Marker (14) TecNiq LED chrome trim rings IATS rubber grommets, p/n: S33-0S00-1	26
99-1059	Lights: Indicator, (1) Whelen 2"TOR00FFR 5mm LED Red with TFLANGEC Chrome Flange - to light up when emergency lights are on. Locate in cab ceiling, install as close as possible to the center of the ceiling.	132
99-1054	Lights: Stepwell, Maxxima 4" model M84443, flush mount LED, ILOS	40
300060	Lights: Turn Arrows, (2) Whelen 600 Series Amber LED PN: 60A00TCR, with chrome flange, mounted on front wall. IATS Location: Must Specify Exact Location	363
300050	Lights: Turn Arrows, (2) Whelen 700 Series Amber LED with chrome flange on front wall below outboard emergency flasher. PN: 70A00TAR IATS	330
99-0909	Lights: Turn Arrows, (2) Whelen M6TC Amber LED with clear lens and chrome flange mounted on front wall below outboard warning lights. IATS	363
99-0764	(1) Camera System: ASA Electronics / VCMS104i - (1) Flush Mount Camera/White, VOM73MM - 7" Rear View Mirror Color Monitor w/brightness, contrast and volume adjustment controls, CEC34 - 32ft. Cable. Locate: (1) Camera mounted off lower RH corner of center rear Amber light; Monitor mounted on cab windshield rear view mirror.	660
99-0774-1	(1) Camera System: ASA Electronics / VCMS104i - (1) Flush Mount, non-adjustable, Camera/White, AOM713 - 7" Rear View, pedestal mount color monitor with brightness, contrast and volume adjustment controls, 9" pedestal mount 77-09SF, CEC34 - 32ft. Cable Locate: Camera mounted off lower RH corner of center rear Amber light; Monitor mounted on passenger side of front condole.	792
99-0765	(2) Camera System: ASA Electronics / VCMS104i - (1) Flush Mount Camera/White, (1) VCMS155 Camera with Manual tilt bracket, VOM73MM - 7" Rear View Mirror Color Monitor with brightness, contrast and volume adjustment controls, CEC34 - 32ft. Cable Locate: (1) Camera mounted off lower RH corner of center rear Amber light, (1) Camera mounted on upper bulkhead wall and Monitor mounted on cab windshield rear view mirror.	792
99-0774-2	(2) Camera System: ASA Electronics / VCMS104i - (1) Flush Mount Camera/White, (1) VCMS155 Camera with Manual tilt bracket, VOM73MM3 - 7" Rear View, pedestal mount color monitor with brightness, contrast and volume adjustment controls, 9" pedestal mount 77-09SF, (2) CEC34 - 32ft. Cables Locate: Camera mounted off lower RH corner of center rear Amber light; Monitor mounted on cab windshield rear view mirror.	1023

99-2574	125 VAC: Duplex Outlet, Grey outlet w/Carbon Fiber finish faceplate, IATS for Gen-T Models. Specify Location:	99
99-1586	125VAC: Hospital Grade 20A DuAcrylic receptacle with (2) USB receptacles, IATS	132
99-2574	125 VAC: Duplex Outlet, Grey outlet w/Carbon Fiber finish faceplate, IATS for Gen-T Models. Specify Location:	46
99-0076	12VDC: 12 gauge power & ground, IATS Specify Location(s):	59
99-0707	Alarm: Door Open, audible BUZZER to alert driver when any compartment or module entry door is open and the chassis is placed in drive. Alarm is deactivated when the unit is in park/neutral.	66
99-1027	Alarm: Emergency parking, this audible alarm will sound only when the vehicle is in park with ignition on and when the parking brake is not set.	165
99-0747	Antenna: (2) 25' Coax with 3/8" through-hole antenna bases prewired to roof ILOS standard coaxial cables. NOTE: Radio installation tech will have to drill hole and complete mount. Install Standard Power/Ground for each behind driver's seat.	145
400010	Antenna: Coax, with 12VDC Power and Ground. IATS Specify Location(s):	46
99-2525	Anti-Theft Device: IdleLock Ignition Security System, Gen-T PN: 32-01-1113 / Intermotive PN: A-IDLE611 for G-3500/4500 Series Chassis Only. Locate activation button to the right side of the steering wheel.	297
99-1761	Anti-Theft Device: IdleLock Ignition Security System, PN: A-IDLE502-A for Ford E Series Chassis Only. Locate activation button to the right side of the steering wheel.	330
99-1759	Anti-Theft Device: IdleLock Ignition Security System, PN: A-IDLE-654-A for C/K 3500 Series Chassis Only. Locate activation button to the right side of the steering wheel.	330
99-1762	Anti-Theft Device: IdleLock Ignition Security System, PN: A-IDLES516-A for Ford Transit Chassis Only. Locate activation button to the right side of the steering wheel.	330
99-1760	Anti-Theft Device: IdleLock Ignition Security System, PN: B-IDLE505-A for Ford F-Series Chassis Only. Locate activation button to the right side of the steering wheel.	330
99-2526	Anti-Theft Device: IdleLock Ignition Security System, PN: C-IDLE750-A for RAM 3500/4500/5500 Series Chassis Only. Locate activation button to the right side of the steering wheel.	297
99-1856	Anti-Theft: TREMCO anti-theft device for Ford, Chevy Only. Ignition security system, locate activation button to the right side of the steering wheel column.	257
400150	Battery Charger: DELETE STANDARD (when adding Inverter with integral charger)	0
99-0142	Battery: (1) Additional, OEM, 650 C.C.A. with Dual Roll-out Tray and Emergency Start Switch for Type 3 conversion only. Locate: In dual battery tray in sealed compartment below ALS. The standard battery under the hood is to be isolated as "Chassis Only" battery. The (2) batteries in the roll-out tray are to be "Conversion Only". There will be a switch in front console labeled "Emerg Start" PN:MX09128. Requires 200-amp continuous duty solenoid and isolator, Power Engineering PST-SBI-3112.	568
99-0766A	Battery: (1) Additional, OEM, 750 C.C.A. with single roll-out tray on Type 1, IATS batteries under the hood. Battery to be located below ALS in sealed storage area.	799
99-0766B	Battery: (2) Additional, OEM, 750 C.C.A. with dual roll-out tray on Type 1, IATS batteries under the hood. Batteries to be located below ALS in sealed storage area.	1102
99-0139	Battery: Jumper cable system terminated in lower portion of front OEM grille Locate: Cables through front grille with connector on top of bumper. Use Vanner connectors on both ends of Ship Loose cable.	264
99-1484	Carbon Monoxide Detector: First Alert Location: Rear wall up high above foot end of squad bench	99
99-0452	Clock: Digital, Intellitec Emergency Timer 00-00775-100. Must Specify Location:	561
99-1192	Clock: Timex 75071TA2 13.5 digital clock Digital Emergency Vehicle Clock installed on mounting panel centered in cabinet over rear doors. (Order backer plate p/n: 33-104400) (Cannot be used on rear overhead w/upper rear main cabinet restocking face)	198
99-2466	Clock: TrinTec 6" Analog Emergency Vehicle Clock with Gen-T Logo and Backlight, EMC-M. Locate:	225

99-1584-EX	Decontamination: AeroClave ADP-EX ambulance decontamination system with wall mounted internal nozzle and flush mount external panel mount port system with weather resistant cover. Location: Must Specify Mounting Points	1452
400250	Electric Step: Kwiikee 26 series - Curbside Entry Door Note: Rubber Mud Flap to be installed forward of the step to protect electrical connections and folding mechanism.	693
99-0093	Electric Step: Zico VS-24-9 retractable vehicle step mounted below curbside entry door. Includes (1) override switch mounted on wall at curbside entry door.	3016
99-1955	Fan: Ventilation. (1) Mechantronics Fan Axial 120x25MM 12VDC fan PN: E1225E12AB-FSR mounted on cabinet door or side wall when any inverter is mounted in an interior, enclosed cabinet.	66
99-2368	Flashlight: Install (1) Customer Supplied flashlight - Requires running 12v. power/ground from electrical above (option 99-0076). Specify Location:	99
99-1623	Flashlight: Streamlight Litebox Model #45871 E-Spot Vehicle Mount system with mounting rack for charging - Yellow. Specify Location:	429
400130	Heater: 125VAC Broan Heater, mounted in EVS Tech seat base designed for a heater. Note: 750 Watt installation requires a 20amp shoreline and 1500 Watt installation requires selecting a 30-amp shoreline ILOS; separate options.	449
99-0917	Heater: 125VAC Broan heater, mounted on aisle side of the squad bench face at the head of the bench. Note: 750 Watt installation requires a 20amp shoreline and 1500 Watt installation requires selecting a 30-amp shoreline ILOS; separate options.	277
400110	Hour Meter: Analog, Engine Specify Location:	112
400115	Hour Meter: Digital, Engine Specify Location:	66
400160	Inverter: Vanner 20-1050CUL- 1000watt w/battery charger and built in GFI. Remote controlled w/switch in rear panel. (This option deletes the GFI in the A/A wall). ILOS NOTE: OPTION 99-1955 IS REQUIRED WHEN ANY INVERTER IS MOUNTED IN ANYBULKHEAD or INTERIOR INCLOSED CABINET. Location: Must specify location.	1584
99-1626	Inverter: Xantrex 807-1050 1000W True Sine Wave Inverter with built in GFI and 55Amp 3 stage battery charger ILOS on TRVG Transit only. Includes 33-10-4686 mounting bracket. Location: Must Specify	1049
99-0215	IV Warmer: Smithworks, 4L Model mounted in cabinet Location: Must provide mounting location	858
99-0688	Lighting: Action Area, Whelen PSCOADCR LED Strip light mounted on 33-102449 stainless steel mounting bracket in 2nd action area IATS.	152
99-0661	Lighting: Cabinet, (1) TecNiq D04-B001-1 Linear Dragon Light Vertical, Blue LED with white case (D04-0WV0-1), 36" wire. Will have Rocker On/Off Switch in Rear Panel, labeled "Cabinet Lights" (MX09188) - operates all at same time. Price per light. Locate LEDs just inside front top corner of each cabinet. NOT ON BACK WALL. Run wires from entry point on the upper rear cabinet corners and along the upper cabinet corners to each LED. Loom the wires and attach with P-clamps. Cabinet Locations: Must Specify	66
99-0599	Lights: Accent, TecNiq Oval Dragon, Blue, D14-B0001-1 with SS case, 36" wire with switch labeled "Cabinet Lights" PN:MX09188 in rear switch panel Location: Must Specify cabinet location(s)	59
99-0835	Lights: Compartment, Optronics ILL36CB LED mounted in exterior compartment IATS	66
99-0525	Lights: Dome, (3) center Whelen 9-diode white/blue LEDs PN: 80CBEHCR, (6) White diodes, (3) Blue diodes in each dome light w/chrome flange- ILOS white LEDs. Switch for "Center" domes only PN: 39-10-9177 labeled White at top / Center / Blue at bottom. NOTE: Gen-T Models Only with 11 LED dome lights.	165
99-0710	Lights: Dome, Aurora 4" dimmable red/white LED, installed on cab headliner, wired ignition hot.	224
99-0989	Lights: Dome, Install temporary switch in electrical cabinet to activate Commander 400 battery disconnect switch when unit is being used for shows. Switch should be installed so that it is easily removable when the show is over and will not be left in the unit.	53

99-0522	Lights: Dome, Whelen LED, 18-diodes with chrome flange MX80EHZA , switched separately with Hi/Lo functions- ILOS	79
99-0567	Lights: Ground, (1) TecNiq E10-WS00-1, LED with angled stainless steel mounting bracket. Location: Must Specify	125
99-1302	Lights: Scene/Load, Whelen M6ZC LED Linear-LED with chrome flange included- ILOS 600 series LED (To be used with the M-series Warning light package). Specify Locations: Rear Load Lights	172
99-1293	Lights: Scenes/Load - Wire the side scene lights to come on anytime an exterior compartment of that side is open, (anytime a streetside compartment is opened the streetside scene lights come on; if side entry door is opened the curbside scene lights come on, etc.) (Please keep the curbside scene light override switch by the side entry door).	165
99-1789	Lights: Shoreline Indicator, Green 125VAC LED Location: Mounted above shoreline inlet on side of module	99
99-0014	Lights: Shoreline Indicator, Red 125VAC LED Location: Mounted above shoreline inlet on side of module	99
99-1558	Lights: Spotlight, 300,000 CP handheld, hard wired, with momentary On/Off switch, located in cab. Able 2 PN: 06-300	125
99-0277	Lights: Warning, (3) Door Open, (1) each entry door. Whelen 2" T0A00FAR 5mm LED Amber w/TGROM2 rubber grommet Locate: (1) on each lower outboard corner of open rear doors; (1) on lower outboard corner of open Curbside Entry door. All three located above the kickplates. Light to flash when door is open.	429
99-0743	Lights: Warning, Compartment Door Open: Whelen 3" 3SA00FAR 5 MM LED AMBER with 3FLANGEC surface mount chrome flange Locate: In cab ceiling between driver and passenger, light to flash when compartment doors are open	158
99-1883	Lights: Warning, Door Open, (3) Whelen 700 Series Red Super-LED with chrome flange- IATS Specify Lens Color: CLEAR Specify Location: (1) each on lower outboard corners on interior door panels of: Curbside Entry Door and Rear Entry Doors. Lights to flash when doors are Open.	594
99-0898	Module Disconnect: (3) way module power control with SPDT momentary switch PN: MX09210 (1) in front console and (1) in rear console. Power can be controlled from either location.	132
99-0813	Radio: Install (1) set of customer supplied radio cables. (NOTE: All cables must be delivered to Gen-T prior to production start date.) Location: Must supply configuration and termination location.	132
400200	Refrigerator: NorCold NR740BB 12VDC/125VAC w/power cord PN: 635591. Locate in ALS Cabinet. Includes cabinet modification, wiring and venting	1188
99-0815	Shoreline: 125VAC, 20 Amp, 60 Hz TwistLock inlet with hinged, waterproof cover ILOS. Located on the streetside wall above compartment #2.	165
99-0169	Shoreline: 125VAC, 20-Amp, 60 Hz, straight blade w/hinged, weatherproof cover. IATS NOTE: Must specify function and location.	198
99-0317	Shoreline: 125VAC, 30-amp, 60 Hz, Twist-Lock- IATS LOCATION: Must Specify	376
2542	Shoreline: Angled housing mounted on the front of the module for the 125 VAC, 20-Amp, Kussmaul SUPER Auto Eject P/N: 091-55-20-120-BW BACK wired w/hinged, yellow, weatherproof cover. Locate the angled housing PN: #33-11-3933 on the front wall of the module adjacent to the driver's entry door and inboard of the corner extrusion so that it does not interfere with opening or closing the cab entry door when the shoreline is plugged into the receptacle. For ease of access, the shoreline receptacle will be mounted on a custom Gen-T stainless steel E-Z mounting plate P/N: 33-11-4310. There will be a green LED indicator light located above the shoreline receptacle. ILOS The mating connector to be shipped loose. A Kussmaul single bar graph display PN 091-94-12 will be installed at the top of the angled bracket above the S.S. plate. Wire the bar graph directly to the onboard 12VDC battery system so that it reads the charge level at all times. NOTE: GEN-T models only.	570
400220	Shoreline: 125VAC, 30-Amp, 60 Hz, Twist-lock inlet w/hinged, weatherproof cover- ILOS	273

99-0621	Shoreline: 125VAC, Kussmaul 15amp SUPER Auto Eject P/N: 091-55-15-120 side wired w/hinged, yellow, weatherproof cover, located above Compartment #2 on Streetside. Mount on a Kussmaul Stainless Steel E-Z mounting plate P/N: 091-185-009 w/indicator light for ease of access. Mating connector to be shipped loose. ILOS NOTE: Must specify function and location.	594
99-0735	Shoreline: 125VAC, Kussmaul 20amp SUPER Auto Eject P/N: 091-55-20-120 side wired w/hinged, yellow, weatherproof cover, located above Compartment #2 on Streetside. Will have to be mounted on a Kussmaul Stainless Steel E-Z mounting plate P/N: 091-185-009 w/indicator light for ease of access. Mating connector to be shipped loose. IATS NOTE: Must specify function and location.	708
99-0617	Shoreline: 125VAC, Kussmaul 20amp SUPER Auto Eject P/N: 091-55-20-120 side wired w/hinged, yellow, weatherproof cover, Located above Compartment #2 on Streetside. Will have to be mounted on a Kussmaul Stainless Steel E-Z mounting plate P/N: 091-185-009 w/indicator light for ease of access. Mating Connector to be shipped loose. ILOS NOTE: Must specify function and location.	594
99-1084	Shoreline: 125VAC, Kussmaul 30amp SUPER Auto Eject P/N: 091-159-30-120-081 side wired w/hinged, yellow/weatherproof cover, located above Compartment #2 on streetside. Will have to be mounted on the Kussmaul stainless steel E-Z mounting plate PN: 091-159-081-120 w/indicator light for access. Kussmaul P/N: 091-159-CON-3P-120 mating female connector to be shipped loose. IATS NOTE: Must specify function and location.	1155
99-0816	Speakers: Speakers wired to OEM radio in cab to be installed in the patient compartment w/Fader control. Located in ceiling, rear of dome lights (see print). Fader control located to the right of the standard outlets in the action area. NOTE: Use special speakers for ceiling (Jensen 5" Model # 1102094W dual cone, entry level speaker. Add aluminum backer plates to roof: (2) 9 3/4" x 1/8" x 4" and (2) 10 1/2" x 1/8" x 4". NOTE: Gen-T 171 Only	244
400190	Speakers: Speakers wired to OEM radio in cab to be installed in the patient compartment with fader control on action area panel. Speakers to be mounted in the rear overhead cabinet.	231
99-0893	Suction, Cover: Rubberized urethane coated smooth aluminum cover to be installed over suction pump for protection in compartment #2. See print: #33-102999 - Make sure to test fit before installing components! Note: Does not fit over inverters.	99
99-0284	Switching: (2) Module Disconnect w/Red Bezel, 3-Way "ON/ON" switches P/N: MX09174 located in (1) in rear switch panel IATS and (1) in front switch panel ILOS. Locate in the far right hand blank switch position on rear switch panel. Requires three additional wires from front console to rear console. Switches will not have an off position.	99
99-1024	Switching: (2) Momentary Switches PN:MX09150 for 3-Way switching of center Dome Lights on Gen-T, (1) located in driver's console and (1) in the standard center dome light position on rear switch panel both wired through an Intermotive control module PN: PRN405-AX.	627
99-0773	Switching: Air Horns, use 3 selection switch PN:MX09189 on front console ("Siren/Air Horn/Horn") to select function for horn ring activation on the steering wheel ILOS ("Horn/Siren"), Delete's air horn momentary switch PN:MX09102 on front console.	66
99-1782	Switching: Duplicate switches on CS Wall: (1) SS Domes; (1) CS Domes in etched plastic bezel: MX01582 Location: Must Specify	231
99-0738	Switching: Electric Step Override, single On/Off switch labeled "Step Override" PN: MX09182 on Positron Panel PN: MX01534, mounted on CS wall at head of Squad Bench	106
99-0404	Switching: Momentary Disable for Scene/Load Lights PN: MX09144 and Power Doors Locks PN: MX09145. Locate: (1) horizontal, 2-position Positron panel (MX01485) on Curbside Wall at head of bench and (1) stacked, 2-position Positron switch panel (MX01520) on wall at curbside rear entry door in standardized position.	297
99-0348	Switching: Momentary for Inverter, mounted in front console switch panel (no "OFF" position on switch) P/N: MX09211 Locate: In Front Console- Labeled "INVERTER".	99
99-0754	Switching: Power Door Locks Only, (2) door lock switches, MX09145: (1) located in a horizontal 2-switch Positron panel, MX01538, in standardized position on Curbside Wall above head of bench; (1) located in single-position Positron switch panel, MX01534, on wall at curbside rear entry door in standardized position.	211

99-0804	Switching: Power Door Locks, Lock/Unlock rocker switch PN: MX09145 located in the front switch panel to unlock and lock the module doors from inside the cab. NOTE: Chevy Type I Models	99
99-0550-M	Switching: Timer, Momentary 15-Minute timer switch for patient compartment dome lights. Locate switch in Positron switch panel in standard position on curbside wall. (PNs: MX09150 switch, MX09151 Timer, MX01507 four position switch panel.) NOTE: Gen-T Models Only	117
99-0550-A	Switching: Timer, Momentary 15-Minute timer switch for patient compartment dome lights. Locate switch in Positron switch panel in standard position on curbside wall. (PNs: MX09150 switch, MX09151 Timer, MX01511 one position switch panel.) NOTE: A-Line Models Only	117
99-0356	Temperature Control Cabinet: Dometic CD-030DC-D65A Drawer, Black. Includes cabinet modification, wiring and venting. Non-Locking Drawer - Order with compressor unit on side and stainless steel cover panel with louvers PN: 33-115154 for RP-90, 154 & 167 models - Order black powdercoated cover panel with louvers PN: 33-113596 for Gen-T models only. Order louvered vent cover for the ALS outboard wall for venting, see print #33-104716. Specify Location:	1155
99-2179	Temperature Control Cabinet: Dometic CD20-DCTB1 Drawer, Black. Includes cabinet modification, wiring and venting. Non-locking Drawer - Order with compressor unit on REAR and stainless steel cover panel with louvers PN: 33-115154 for RP-90, 154 & 167 models; order #33-103736 for Gen-T models only. Order louvered vent cover for the ALS outboard wall for venting, see print # 33-104716. Specify Location:	1518
99-0897	Temperature Control Cabinet: Dual Temp Horizontal, Mermaid MK DT/H - Micro Depth with back mount compressor. Install per manufacturer's instructions regarding power supply (two individually fused power sources), fan and ventilation! (See option in cabinet section for cabinet modification charge). NOTE: Make sure cabinet build prints have the ventilation on back wall and outboard side wall of ALS cabinet.	4891
99-0453	Temperature Control Cabinet: Medi-Kool MK-Saline SS with side-mounted compressor. Order with door hinged on bottom so it flips down and with key lock cylinder. Temperature control panel will be installed on S.S louvered panel, front of ALS cabinet, to the right of the Medi-Kool cabinet. Includes cabinet modification, wiring and venting. Requires a S.S. panel to cover the right side of the large access hole. See 33-103092.	4125
99-0337	Temperature Control Cabinet: Medi-Kool Stainless Steel model 15 SS with back-mounted compressor and 1" mounting flange with controls. Faceplate will be installed at top of Medi-Kool cabinet and compressor will be located directly behind it. Order with door hinged on right hand side. Standard lock and handle. Unit to be installed in ALS cabinet per attached drawings. NOTE: Make sure cabinet build prints have the ventilation on back wall and outboard side wall of ALS cabinet.	4244
99-0994	Timer: Intermatic FD30MHW 30 minute spring wound rotary style timer with "HOLD" feature wired to patient compartment dome lights. Location: Must Specify	139
99-0988	USB Port: Kussmaul 091-219-N dual USB port mounted in switch panel. Fits into standard switch slot. IATS LOCATION: Must Specify	132
99-0742	USB Port: Vanner VSS-USB Flush Mount (2) port USB Receptacle.. IATS LOCATION: Must Specify	99
99-0999	Lights: Warning, (1) Whelen M2WD Series Red/White Super LED with clear lens and chrome bezel M2FC, IATS above rear wheel well as rear intersection lights. Wire to Primary circuit only.	257
99-1092	Lights: Warning, Grille, (2) Whelen 500 V Series 5V1R LED Single color, Red with chrome flanges 5LSMAC - ILOS, in front grille. Wire with constant power so internal flasher flashes light. NOTE: Ford "F" Series, All GM Series.	568
99-0045	Lights: Warning, Whelen 700 Series Red/Amber Super LED 70RA6FCR, ILOS on front fender	297

99-1359	<p>Lights: Warning, Whelen M-Series LED EMERGENCY Lighting Package ILOS Whelen LED warning Package- Ford, Chevy Type I and Type III - RP-90, 154 and 167 - Models ONLY.</p> <p>NOTE: Does not include LED Scene or Load Lights.</p> <p>All LED lights shall have CLEAR Lenses. All emergency and scene lighting shall have chrome flanges in standard locations.</p> <p>Front of Body: Add (7) M9 Whelen LEDs- Specify pattern by LED Color (Red or White): Configured R/W/R/W/R/W/R or R/R/R/W/R/R/R (Must provide configuration). (4) M9 Red LEDs & (3) M9 White, (2) outer corners and (1) center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console.</p> <p>Sides of Body: (4) M9 Red LEDs: (2) each side in upper corners</p> <p>Rear of Body: (4) Whelen M-Series Red LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level, (1) Whelen M-Series Amber LED in the center position over the rear doors.</p> <p>Brake, Turn & Back-Up Lights: M6 LEDs</p> <p>Lights, Warning, Intersection Lights: (2) M7 Red LEDs on Front Fenders wired to Primary/Sec Modes</p>	3036
99-1358	<p>Lights: Warning, Whelen M-Series LED EMERGENCY Lighting Package ILOS Whelen LED warning Package- Ford, Chevy Type III Gen-T and Ford and Dodge Type I - Gen-T Models ONLY.</p> <p>NOTE: Does not include LED Scene or Load Lights.</p> <p>All LED lights shall have CLEAR Lenses. All emergency and scene lighting shall have chrome flanges in standard locations.</p> <p>Front of Body: Add (7) M9 Whelen LEDs- Specify pattern by LED Color (Red or White): Configured R/W/R/W/R/W/R or R/R/R/W/R/R/R (Must provide configuration). (4) M9 Red LEDs & (3) M9 White, (2) outer corners and (1) center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console.</p> <p>Sides of Body: (4) M9 Red LEDs: (2) each side in upper corners</p> <p>Rear of Body: (4) Whelen M-Series Red LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level, (1) Whelen M-Series Amber LED in the center position over the rear doors.</p> <p>Brake, Turn & Back-Up Lights: M6 LEDs</p> <p>Lights, Warning, Intersection Lights: (2) M7 Red LEDs on Front Fenders; (2) M7 Red LEDs above rear Wheel Wells- wired to Primary/Sec Modes</p>	3234
99-0178	Siren: Whelen 295 HFS2 electronic siren with 100/200 watt remote siren amplifier, ILOS	231
99-1327	<p>Speaker: Siren, (2) ES100 100 Watt speaker with (2) 33-105072 mounting brackets installed. ILOS</p> <p>Location: Must specify</p> <p>NOTE: Ford E-Series Only.</p>	198
99-1737	<p>Lightbar: Rear Fiberglass Pod ILOS with (5) Whelen 700 Series Super-LEDs: (2) outboard-70R02FCR Red, (2) inboard-75COENZR LEDs and (1) center-70A02FCR Amber on custom designed rear fairing mounted to the OEM roof above the rear doors. Wire Red LEDs primary/secondary and the Amber LED to Primary mode only.</p> <p>NOTE: Rear loads to illuminate when the vehicle is in reverse.</p> <p>NOTE: Transit Type II Only</p>	132
99-0106	Lights: Scene/Load, Rear side scene lights on each side to come "ON" in Reverse	66
500125	<p>Lights: Scene/Load, Whelen 600 Series Halogen</p> <p>Gradient Opti-Scenelight™ with chrome flange- IATS</p> <p>Specify Location:</p>	117
99-0374	Lights: Scene/Load, Whelen 600 Series Super-LED® Gradient Opti-Scene LED 6SCOENZR with chrome flange 6EFLANGE , ILOS 900 Series Halogen	198
99-1150	<p>Lights: Scene/Load, Whelen 700 Series Halogen Gradient Opti-Scenelight™ 70K000ZR - IATS</p> <p>Locate: (1) each side, centered between front and rear Scene lights</p>	172
99-0282	Lights: Scene/Load, Whelen 700 Series Super-LED® 70COENZR "surface mount" with chrome flange 7EFLANGE - ILOS 900 Series Halogen	198
500120	<p>Lights: Scene/Load, Whelen 900 Series Halogen</p> <p>Gradient Opti-Scenelight™ with chrome flange- IATS</p> <p>Specify Location:</p>	117
500127-A	<p>Lights: Scene/Load, Whelen 900 Series Super-LED 9SCOENZR Gradient Opti-Scenelight™ with chrome flange 9EFLANGE - IATS</p> <p>Specify Locations:</p>	475

500127	Lights: Scene/Load, Whelen 900 Series Super-LED 9SC0ENZR Gradient Opti-Scenelight™ with chrome flange-ILOS Halogen Specify Locations:	429
99-0968	Lights: Scene/Load, Whelen M7ZC Gradient Scene light with chrome flange, ILOS 900 Series Halogen.	297
99-0700	Lights: Scene/Load, Whelen M9 Linear Super-LED® Surface Mount M9LZC with chrome flange M9FC- ILOS Halogen Specify Locations:	475
99-0937	Lights: Warning, (1) Whelen 500 Series Super-LED 50C02ZCR White with chrome flange 5LSMAC IATS Specify Location(s):	198
99-0651	Lights: Warning, (1) Whelen 500 Series Super-LED 50CR2ZCR Red/White with clear lens. IATS Location: Must specify	297
99-1380	Lights: Warning, (1) Whelen 700 Series Super-LED 70C02FCR White with clear lens and chrome flange, IATS Must specify location:	257
99-0933	Lights: Warning, (1) Whelen 900 Series Super-LED 90BB5FCR Blue with clear lens and chrome flange. IATS Location: Must Specify	310
500190	Lights: Warning, (1) Whelen 900 Series Super-LED 90RR5FCR RED with clear lens, IATS Specify Location:	297
99-0870	Lights: Warning, (1) Whelen LINZ6B Blue Super-LED with clear lens & chrome flange. IATS Specify Location:	178
99-0876	Lights: Warning, (1) Whelen M2WRC Series Super-LED M2WRC Red with clear lens and chrome flange M2FC, IATS above rear wheel well as rear intersection lights. Wire to Primary circuit only.	251
99-0716	Lights: Warning, (1) Whelen Micron Series Super-LED MCRNSCC White with chrome flange. IATS mounted on OEM Grille	264
99-0715	Lights: Warning, (1) Whelen Micron Series Super-LED MCRNSCR Red with chrome flange. IATS mounted on OEM Grille	264
99-0643	Lights: Warning, (1) Whelen Wide Angle Super-LED WIONSMCC White LED with Chrome Housing mounted in grille - IATS	251
99-0642	Lights: Warning, (1) Whelen Wide Angle Super-LED WIONSMCR Red LED with Chrome Housing mounted in grille - IATS	251
500200	Lights: Warning, (2) Whelen 600 Series Super-LED 60R02FCR Red with clear lens, IATS Specify Location:	396
500210	Lights: Warning, (2) Whelen 700 Series Super-LED 70R02FCR Red with clear lens and chrome flange 7EFLANGE, IATS above rear wheel wells as rear intersection lights. Wire to Primary circuit only.	396
99-0869	Lights: Warning, (2) Whelen 700 Series Super-LED 70RA6FCR Red/Amber with chrome flange, IATS (1) above each rear wheel well as rear intersection lights. Wire to Primary circuit only.	713
99-0112	Lights: Warning, (2) Whelen 700 Series Super-LED 70RC6FCR Red/White with chrome flange, IATS (1) above each rear wheel well as rear intersection lights. Wire to Primary circuit only.	594
99-0750	Lights: Warning, (2) Whelen 900 Series Super-LED 90BB5FCR Blue LEDs, IATS NOTE: Must add chrome flange separately.	521
99-2339	Lights: Warning, (2) Whelen ION Mini-T Super-LED, Blue TLMIB with clear lens and chrome flange located on OEM grille IATS. Must specify flash pattern. Location(s): Must Specify	330
99-2343	Lights: Warning, (2) Whelen ION Mini-T Super-LEDs, Red TLMIR with clear lens and chrome flange located on OEM grille IATS. Must specify flash pattern. Location(s): Must Specify	330
99-2344	Lights: Warning, (2) Whelen ION Mini-T Super-LEDs, White TLMIC with clear lens and chrome flange located on OEM grille IATS. Must specify flash pattern. Location(s): Must Specify	330
99-0739	Lights: Warning, (2) Whelen Micron Series Super-LED MCRNSR Red with Black flange mounted over rear doors on Transit. IATS	436
99-0670	Lights: Warning, Grille, (1) Whelen LINZ6C Clear Super-LED & chrome flange on center grille bar, IATS Specify Location:	178
99-0680	Lights: Warning, Grille, (1) Whelen LINZ6D Red/Clear Super-LED with clear lens & chrome flange. IATS Specify Location:	178

99-0671	Lights: Warning, Grille, (1) Whelen LINZ6R Red Super-LED with clear lens & chrome flange on center grille bar. IATS Specify Location:	178
99-0650	Lights: Warning, (1) Whelen 500 Series TIR6 Super-LED 50RC3ZCR Red/White LED with chrome flange and clear lens mounted on grille. ILOS LINZ6	132
99-0801	Lights: Warning, (1) Whelen 700 Series Super-LED 70B02FCR Blue LED, ILOS 700 Series Red Super-LED 70R02FCR on Transit. NOTE: Must specify location	66
99-0802	Lights: Warning, (1) Whelen 700 Series Super-LED 70RA6FCR Red/Amber with clear lens, ILOS 700 Series Super-LED 70R02FCR Red on Transit. NOTE: Must specify location	211
99-0948	Lights: Warning, (1) Whelen 700 Series Super-LED 70RB6FCR Red/Blue with clear lens, ILOS 700 Series Super-LED 70R02FCR Red in standard LED Package. NOTE: Must specify location	231
99-0978	Lights: Warning, (1) Whelen 700 Series Super-LED 70RC6FCR Red/White with clear lens, ILOS 700 Series Super-LED 70R02FCR Red in standard LED package. NOTE: Must specify locations	198
99-0809	Lights: Warning, (1) Whelen 900 Series Super-LED 90BB5FCR Blue, ILOS 900 Series Super-LED 90RR5FCR Red. NOTE: Must specify locations	33
99-0979	Lights: Warning, (1) Whelen 900 Series Super-LED 90RA5FCR Red/Amber, ILOS 900 Series Super-LED 90RR5FCR Red. NOTE: Must specify location	218
99-0811	Lights: Warning, (1) Whelen 900 Series Super-LED 90RC5FCR Red/White, ILOS 900 Series Super-LED 90RR5FCR Red. NOTE: Must specify location	185
99-1137	Lights: Warning, (1) Whelen ION Series Wide Angle Super LED WIONSMC White LED with chrome flange ILOS LINZ6 Series Super LED LINZ6R with chrome flange. NOTE: Must Specify Location	119
99-0406	Lights: Warning, (1) Whelen ION Series Wide Angle Super LED WIONSMC White LED with chrome flange. IATS NOTE: Must Specify Location	304
99-1124	Lights: Warning, (1) Whelen ION Series Wide Angle Super LED WIONSMR Red LED with chrome flange ILOS LINZ6 Series Super LED LINZ6R with chrome flange. NOTE: Must Specify Location	119
99-0405	Lights: Warning, (1) Whelen ION Series Wide Angle Super LED WIONSMR Red LED with chrome flange. IATS NOTE: Must Specify Location	304
99-0674	Lights: Warning, (1) Whelen LINZ6 Series Super-LED LINZ6D Red/Clear LED with clear lens on center grille bar. ILOS LINZ6 Super LED LINZ6R Red. NOTE: Must Specify Location	112
99-0964	Lights: Warning, (1) Whelen M7 Series Super-LED M7DC Red/White LED with chrome flange, ILOS M7RC Red LED over rear wheels in M Series option package. NOTE: Gen-T Models Only	66
99-2016	Lights: Warning, (1) Whelen M7 Series Super-LED M7RC Red LED with chrome flange ILOS LINZ6R. Location: Must Specify	112
99-0967	Lights: Warning, (1) Whelen M9 Series Red/White Super-LED M9DC Red/White with chrome flange, ILOS M9 Series Super-LED M9RC Red in M Series Option Package. NOTE: Must specify locations	66
99-1090	Lights: Warning, (1) Whelen M9 Series Super-LED M9BC Blue with chrome flange, ILOS M9 Series Super-LED M9R Red in M Series Option Package. NOTE: Must specify location	66
500315	Lights: Warning, (2) Whelen 500 Series TIR6 Super-LED 50C03ZCR White LED with chrome flange and clear lens mounted on grille. ILOS LINZ6R	132

99-1134	Lights: Warning, (4) Whelen M9 Series Linear LED M9V2R combination Red Super-LED and Scene light with chrome flange ILOS M9RCZ. NOTE: Transit only.	1584
99-0840	Lights: Warning, (5) Whelen M7 Series Super-LED: [2] M7DC White/Red LEDs located on outboard corners of front light pod, [2] M7RC Reds LED located just outboard of center LED and [1] M7C White LED located in the center position with chrome bezels. ILOS 700 Series Super-LEDs. NOTE: Transit Only	561
99-1001	Lights: Warning, (5) Whelen M7 Series Super-LEDs: [4] M7DC Red/White LEDs located outboard of center on front light pod and [1] M7C White LED located in the center with chrome flanges ILOS 700 Series LEDs. NOTE: Transit Only	647
99-2080	Lights: Warning, (6) Whelen PSD01FCR Striplite Plus DUO Super-LEDs, Red/White with clear lens and chrome flange IATS. Specify Location(s): Mount (3) each side of vehicle in lower rub rail - (1) front, (1) just in front of rear wheel and (1) rear per attached drawings. NOTE: Must specify flash pattern (Alternative colors can be programmed separately; flashing or steady burn).	1584
99-2079	Lights: Warning, (6) Whelen PSR01FCR Striplite Plus Super-LEDs, Red with clear lens and chrome flange IATS. Specify Location(s): Mount (3) each side of vehicle in lower rub rail - (1) front, (1) just in front of rear wheel and (1) rear per attached drawings. NOTE: Must specify flash pattern.	1287
99-0868	Lights: Warning, Whelen 900 Series Super LED Red/Blue 90RB5FCR, ILO 900 Series Red Super LED (90RR5FCR)	198
99-0803	Lights: Warning, Whelen 900 Series Super LED Red/Blue 90RB5FCR, ILOS 900 Series White Super LED 90CC5FCR NOTE: Must specify locations -	152
99-0714	Lights: Warning: (2) Whelen Micron Series Super-LED MCRNSCR Red LED with clear lens and chrome flange, ILOS (2) LINZ6 Series LINZ6R Red LEDs and chrome flanges mounted on OEM Grille.	231
99-0271	Lights: Chrome Flange for Whelen M6-Series Light not in package NOTE: Must Specify Location	18
99-0266	Lights: Chrome Flange for Whelen M9-Series Light not in package NOTE: Must Specify Location	26
500410	Lights: Chrome Flange on 900 Series Scene Light when not in package. NOTE: Must Specify Location	20
500400	Lights: Warning, (1) Whelen 700 Series Super-LED 70A02FCR Amber with clear lens and chrome bezel, IATS NOTE: Must Specify Location	172
500390	Lights: Warning, (1) Whelen 700 Series Super-LED 70A02FCR Amber with clear lens and chrome bezel, ILOS 900 Series Super-LED Amber in standard LED package. NOTE: Must Specify Location	33
500370-A	Lights: Warning, (1) Whelen 900 Series Super-LED 90AA5FCR Amber with chrome flange and clear lens, ILOS 900 Series Super-LED Red LED in standard LED package. NOTE: Must Specify Location	33
500380	Lights: Warning, (1) Whelen 900 Series Super-LED 90AA5FCR Amber with clear lens and chrome flange, IATS NOTE: Must Specify Location	297
99-0841	Lights: Warning, (4) Whelen M7 Series Super-LED mounted on the upper rear doors in the Cast Products housing with (1) M7BC Blue with clear lens located outboard on the street side, (1) M7RC Red with clear lens located outboard on the curbside and (2) M7AC Amber with clear lens mounted in the inboard position on each upper rear door housings. NOTE: Requires (4) 33-10-2176 700 Series to M7 Series adapter plates. NOTE: Transit Type II Only	495
500375-A	Lights: Warning: (1) Whelen 600 Series Super-LED 60A02FCR Amber with chrome flange and clear lens, ILOS 900 Series Super-LED Amber LED in standard LED package. NOTE: Must Specify Location	33
500420	Lights: Warning, Wig-Wag, Sound-Off flasher wired to OEM headlights - (includes one switch in front panel, P/N: MX09048) (NOTE: Must select an LED lighting option to go with the flasher. Wig-Wags cannot be wired to OEM headlights.)	112

99-2564	<p>Lights: (14) TecNiq AC00-1 Amber LED Link Lights. Install LED links behind door panels through CNC cutout in the door panel and with a stainless steel bezel on the exterior surface prior to panel installation on to each door. Lights will protrude through CNC cutout and each have a bezel. LED link lights come in 4" sections are designed to be linked together to provide the lengths indicated below. LED links will be wired to (1) Maxxima M50910 flasher mounted inside each door. 12" groups will be wired so that the outboard and center LED links will alternately flash. 8" group will be wired to alternately flash. Each compartment door will be wired so that only the LED links in each single door flash when the corresponding door is open (no other LED links are affected).</p> <p>Specify Location: (3) in top of #4 Compartment door in a 12" cutout. (2) in top of #6 Compartment door in a 8" cutout. (3) in top of #1 Compartment door in a 12" cutout. (3) in top of #2A Compartment door in a 12" cutout. (3) in top of #3 Compartment door in a 12" cutout.</p> <p>NOTE: This option is for compartment doors only and are wired separately from any entry door lighting options.</p>	720
99-2544	<p>Lights: (14) TecNiq D21- RC00-1 Red LED Link Lights. Install LED links behind door panels through CNC cutout in the door panel and with a stainless steel bezel on the exterior surface prior to panel installation on to each door. Lights will protrude through CNC cutout and each have a bezel. LED link lights come in 4" sections are designed to be linked together to provide the lengths indicated below. LED links will be wired to (1) Maxxima M50910 flasher mounted inside each door. 12" groups will be wired so that the outboard and center LED links will alternately flash. 8" group will be wired to alternately flash. Each compartment door will be wired so that only the LED links in each single door flash when the corresponding door is open (no other LED links are affected).</p> <p>Specify Location: (3) in top of #4 Compartment door in a 12" cutout. (2) in top of #6 Compartment door in a 8" cutout. (3) in top of #1 Compartment door in a 12" cutout. (3) in top of #2A Compartment door in a 12" cutout. (3) in top of #3 Compartment door in a 12" cutout.</p> <p>NOTE: This option is for compartment doors only and are wired separately from any entry door lighting options.</p> <p>NOTE: GEN-T 171 model Only</p>	800
99-2264	<p>Lights: (9) TecNIQ D21- AC00-1 Amber LED Link Lights, (3) LEDs mounted at the top section of each of the following door panels with (1) 33-11-4384 stainless steel bezel: a. Both Rear Entry Door Panels b. Side Entry Door Panels</p> <p>Note: Each LED group will be 12" long overall so each door will have three LED lights connected to each other. LEDs will be installed behind the door panel in pre-cut slots designed to accommodate the LED group. There will be (1) Maxxima M50910 flasher module mounted in each door and wired to each LED group. Each group will be wired to "A" / "B" flasher modes so that the Middle and Outer LEDs alternate whenever that individual door is opened.</p> <p>NOTE: GEN-T models only</p>	480
99-1707-F	<p>Siren: Carson SA-441-10F Magforce Electronic Dual Tone Siren ILOS, wired to the standard through bumper speakers. Locate in standard front Type I and III switch panel.</p>	363
99-1029	<p>Siren: Carson SA-441M Magforce Mechanical Dual Tone Siren IATS. Locate in add-on console removable panel. Make sure to order aluminum face plate for add-on console with correct hole size, mounted on right side of panel- See print 44-10-2884. NOTE: Must add additional speakers for SA-441 and specify mounting location.</p>	990
99-1516	<p>Siren: Carson SA-441M Magforce Mechanical Dual Tone Siren ILOS, wired to the standard through bumper speakers. Locate in standard front switch panel.</p>	693

99-1636	Siren: Federal e-Q2B-200 Electronic with (2) ES100 - 100 watt siren speakers with ESB-U mounting bracket, IATS. NOTE: Does not delete standard speakers. Location: Must specify exact mounting location.	3168
99-0790	Siren: Federal Signal, Low Frequency "Rumbler-3" with RB-GVAN11 bracket for G3500/4500 Series mounted on OEM frame, IATS	1069
99-2009	Siren: Whelen 295HFSA7 Remote Dual Siren Amplifier, with Flush Mount Control Head, Meets CA Title 13, ILOS Whelen 295SLSA1 - Order MX01436 front switch panel for correct siren cut-out.	277
99-1191	Siren: Whelen 295SLSA1 Siren IATS, wired to the separate speakers. Locate siren in console removable Positron panel p/n: 39-09-3501 (MX01274). NOTE: Must add additional speakers for additional 295SLSA1 and specify mounting location.	363
99-0354-G	Siren: Whelen Low Frequency "Howler" with HWLRB11 brackets for GM G-Series. NOTE: Includes (2) Speakers.	1155
99-0354-DR	Siren: Whelen Low Frequency "Howler" with HWLRB14 brackets for Dodge Ram Series. NOTE: Includes (2) Speakers.	1155
99-0354-FF	Siren: Whelen Low Frequency "Howler" with HWLRB22 brackets for Ford F-Series. NOTE: Includes (2) Speakers.	1155
99-0354-FT	Siren: Whelen Low Frequency "Howler" with HWLRB23 brackets for Ford Transit. NOTE: Includes (2) Speakers.	1155
99-0354-C	Siren: Whelen Low Frequency "Howler" with HWLRB26 brackets for GM C-Series. NOTE: Includes (2) Speakers.	1155
99-0354-FE	Siren: Whelen Low Frequency "Howler" with HWLRB4 brackets for Ford E-Series. NOTE: Includes (2) Speakers.	1155
99-0708	Lights: Warning, GTT 794H LED Emitter (Supplier P/N: 151-794H). Must be wired to de-activate when the vehicle is in park/neutral. Opticom momentary disable switch PN: C-00058-00-0V1D mounted in the driver's console. (Transit Only) Location: TBD	2607
99-0706	Lights: Warning, GTT 794H LED Opticom Emitter (Supplier P/N: 151-794H) with on/off switch PN: 39-10-9053 in front console. Must be wired to de-activate when the vehicle is in park/neutral. Location: TBD	2541
99-0237	Lights: Warning, Opticom Pre-Wire "ONLY" w/switch PN: 39-10-9053 in front console and wiring secured behind center clear light and configured to de-activate when the vehicle is in Park/Neutral.	132
99-0991	Lights: Warning, Priority Green Opticom Emitter (Supplier P/N: MTER) "ONLY" with on/off switch PN: 39-10-9053 in front console. Must be wired to de-activate when the vehicle is in park/neutral. (Note: For Mods only) Location: TBD	825
600075	Flowmeter: Ohio Medical, FM-15UO-OH with quick disconnect - SHIP LOOSE	119
600010	Medical Air Outlet: Yellow Face Latch Valve Plate w/AD-OHUA-DM Quick Disconnect Fitting inside and DA-HB4-A-DN adapter fitting on yellow hose in Compartment #1 Specify Location(s):	231
99-0763	Medical Air: Oxy-Minder, Medical Air Digital Contents Monitor w/Manual By-Pass and switch on A/A, IATS. NOTE: Requires Option 600010. Location: Must Specify	1056
99-1426	O2 Cylinder Mount: CPI OA1101-D-1 oxygen bottle holder with mounting plate, for "D" cylinders. Specify Location(s):	304
600040	O2 Cylinder Mount: For "M" Cylinder, black steel, for Medical Air or O2 Cylinder- IATS Specify Location(s):	363
99-0741	O2 Cylinder Mount: Install mount for ALUMINUM "M" or "H" cylinder in Compartment #1 ILOS. Mount is adjustable with 3-spring buckle straps and top collar, powder-coated Safety Yellow color. See assembly print 66-A11379 - Rev A	165
600035	O2 Cylinder Mount: M or H Medical Air or O2 cylinders. Adjustable, Safety Yellow bracket w/3-spring buckle straps and top collar- ILOS, Use p/n: 66-A10761 (Standard on Gen-T II) Specify Location(s):	198
99-0376	O2 Cylinder Mount: M or H Medical Air or O2 cylinders. Adjustable, Safety Yellow bracket with 3-spring buckle straps and top collar- IATS - Gen-T II ONLY Specify Location(s):	165

600080	O2 Cylinder Universal Lift: Zico QR-OTSL-US for H-Cylinder, LH Drive, LH Remote Control; Mounting Bracket and Can Cover required: 33-102085 & 33-102074. Specify Location(s):	4374
600090	O2 Cylinder Universal Lift: Zico QR-OTSL-US for M-Cylinder, LH Drive, LH Remote Control; Mounting Bracket and Can Cover required: 33-102085 & 33-102074. Specify Location(s):	4374
600070	Oxygen: Electric O2 with manual bypass and switch mounted on A/A panel	264
600100	Oxygen: OHMEDA Z-QD0101M0 outlet, IATS Specify Location(s):	165
99-0966	Oxygen: Oxy-Minder, Digital Contents Gauge with Manual By-Pass and switch on A/A panel ILOS Electric O2, Deletes standard regulator NOTE: Gen-T & Transit Models Only	759
99-0127	Oxygen: Oxy-Minder, Digital Contents Gauge with Manual By-Pass and switch on A/A panel ILOS NOTE: Deletes standard regulator	997
99-1667	Portable O2 Bracket: (1) CPI OA1201-D-1 strapless oxygen bottle holder with mounting plate, for (1) "D" cylinder. Specify Location(s):	409
99-1668	Portable O2 Bracket: CPI OA1201-E-1 strapless oxygen bottle holder with mounting plate, for "E" cylinders. Specify Location(s):	422
600050	Portable O2 Bracket: Ferno Washington #521 Oxygen Bottle Holder for D-E Cylinder Specify Location(s):	462
99-0320	Regulator: Medical Air, Amvex GR-346, 50 psi, pre-set	132
99-0318	Regulator: O2, Amvex GR-540 50psi, pre-set- IATS	124
99-0912	Suction System: SSCOR wall mount aspirator system with gauge/regulator, SS canister holder and SSCOR electric pump located in compartment #2. Includes vacuum switch with red bezel, located in the 4th position on the curbside wall switch panel- IATS	891
99-0639	Suction System: SSCOR with SS Bracket for container, electric pump- ILOS Rico System NOTE: Locate gauge and Vacuum outlet on action area wall. ILOS	482
99-0133	Suction System: Vacuum Outlet, Ohmeda white face plate plumbed directly to the vacuum pump ILOS Rico wall mount assembly. Includes Ohmeda type quick disconnect suction adapter with 1/8" NPT male threads for connection to the suction gauge.	231
99-2668	HVAC System: UPGRADE TO ADDITIONAL CONDENSER MOUNTED ON ROOF, FRONT WALL OR UNDER CHASSIS	2255
99-1972	HVAC System: UPGRADE TO STAND ALONE SYSTEM INCLUDING ADDITIONAL COMPRESSOR AND CONDENSER MOUNTED ON ROOF, FRONT WALL OR UNDER CHASSIS	6050
99-2588	HVAC System: UPGRADE TO 110VAC/12VDC SYSTEM INCLUDING ADDITIONAL COMPRESSOR AND CONDENSER MOUNTED ON ROOF, FRONT WALL OR UNDER CHASSIS NOTE: MUST SELECT 30AMP SHORELINE OPTION TO POWER THE SYSTEM IN 110AC MODE	9350
99-0214	A-Bar: WITH Sharps/Waste Holders, 15" Wide; .250" Mounting plate. Requires squad bench assembly print different than standard. NOTE: 153 Models Only	482
99-1122-B	A-Bar: WITH Sharps/Waste Holders, 15"W with .250" mounting plate, Powder coated yellow. Requires squad bench assembly print different than standard NOTE: Type I - 171	568
99-1122-A	A-Bar: WITH Sharps/Waste Holders, 15"W with .250" mounting plate, Powder coated yellow. Requires squad bench assembly print different than standard NOTE: Type III - 171	568
99-1028	A-Bar: With single Waste Holder Only, no sharps. 15" Wide with .250" Mounting plate. Requires squad bench assembly print different than standard NOTE: RP-90 Models Only	482
99-0236	A-Bar: WITHOUT Sharps/Waste Holders, 15" Wide with .250" Mounting plate	449
99-0653	Action Area: Custom cabinet below overhead cabinet for customer radio installation. Interior dimensions: 8"H x 5 1/2"D x 40"L with REMOVABLE, BLACK POWDER COATED, ALUMINUM access panel, no latches. Panel will be screwed on. Opening to cabinet to be large as possible, as close to inside dimensions as possible. See PN: 33-103438	257

99-0437	ALS Cabinet: Cabinet above ALS, (1) Cabinet with dual laminated aluminum, hinged doors with (1) non-locking, 2" round Southco stainless steel latch and (1) Adjustable Shelf. ILOS Gen-T II ONLY	264
99-0421	ALS Cabinet: Cabinet above ALS, (1) Cabinet with top, piano-hinged Acrylic door, gas-strut hold-open, (1) non-locking, 2" round Southco stainless steel latch and (1) Adjustable Shelf. ILOS Gen-T II ONLY	264
99-0953	ALS Cabinet: Close off lower section of ALS cabinet for Inside/Access only.	99
800020	ALS Cabinet: Combine Lower and Middle sections into one OPEN section w/ 2 adjustable shelves. A-line mods only. (Must add in option for net to cover opening)	66
99-0903	ALS Cabinet: delete standard slide-out drawer in ALS and combine middle and lower sections into one opening with (3) adjustable shelves, tall dual ½" Acrylic doors with (1) locking, 2" round Southco stainless steel latch at the top of each door. There will be NO latches at bottom of doors per dealer. ILOS NOTE: The standard fixed shelf is changed into an adjustable shelf, there will be a total of (3) adjustable shelves in this section. NOTE: Gen-T ONLY	396
99-0942	ALS Cabinet: delete standard slide-out drawer in ALS and combine middle and lower sections into one opening with (3) adjustable shelves, tall dual solid Acrylic doors with a non-locking two point pinch latch on each door. ILOS NOTE: The standard fixed shelf is changed into an adjustable shelf, there will be a total of (3) adjustable shelves in this section. NOTE: Gen-T ONLY	330
99-0733	ALS Cabinet: delete standard slide-out drawer in ALS and make middle and lower sections equal height with (1) adjustable shelf each section, each section to have dual 1/2" Acrylic doors with a non-locking two point pinch latch on each door. Install dual Acrylic doors on upper cabinet. ILOS NOTE: Gen-T ONLY	759
99-1136	ALS Cabinet: Design GT-154 ALS cabinet similar to Gen-T model. Upper cabinet with hinged 1/2" acrylic doors, (1) non-locking, LifeDefender latch on each door and (1) adjustable shelf; middle drawer with non-locking, LifeDefender latch and the LOWER section to have a dual hinged solid Acrylic doors with non-locking, LifeDefender latch on each door and (1) adjustable shelf. ILOS NOTE: GT-154 Model ONLY	594
99-1857	ALS Cabinet: Lower Locking storage for 747 with LifeDefender latch and LifeDefender key lock; Middle Section with dual 1/2" Acrylic doors with (1) Eberhard two-point pinch latch on each door and (1) adjustable shelf. NOTE: GT-154, RP-90 & MR-90 models ONLY	330
99-0784	ALS Cabinet: Lower section- Locking storage for 747 box with (1) locking, 2" round Southco stainless steel latch. Middle Section to have Drawer (M2 size) with HD slides & (1) non-locking LifeDefender latch. Upper Section to have dual Acrylic doors with polycarbonate inserts, (1) non-locking, 2" round Southco stainless steel latch on each door and 1-adjustable shelf. NOTE: GT-167 Models ONLY	759
99-1078	ALS Cabinet: Move standard slide-out drawer up just below the upper ALS section. Combine middle and lower sections into one opening with (2) additional adjustable shelves, tall dual solid Acrylic doors with non-locking, two point pinch latches on each door. NOTE: The standard fixed shelf is changed into an adjustable shelf, there will be a total of (4) adjustable shelves in this section. ILOS NOTE: Gen-T ONLY	330
99-2540	ALS Cabinet: Delete standard slide-out drawer in middle section. Combine upper, middle and lower section into one storage area w/(2) adjustable aluminum shelves and dual non-locking Austin LifeDefender acrylic doors. Cabinet Above ALS: Open storage w/dual, non-locking Austin LifeDefender acrylic doors w/(1) adjustable aluminum shelf. Shelf to have same flooring as patient area. Note: ALS Doors to be inset and cabinet edge to be wrapped with nosing trim. NOTE: ALL SHELIVING IN THIS CABINET TO BE GEN-T SHELIVING WITH 1" LIPS ON ALL 4 SIDES. NOTE: GEN-T 171 TYPE I ONLY.	250
99-0786	ALS Cabinet: Standard configuration 1/2" HDPE cabinet with door deleted from 747 cabinet area at bottom. NOTE: Transit ONLY	0

99-2428	<p>ALS Cabinet: Combine lower and upper ALS cabinets into one large cabinet with a large pair of side hinged inset acrylic doors and NO pull out drawer. Install a pair of two point pinch latches, one per door. There will be three (3) adjustable shelves inside this cabinet, all with Inside/Outside access.</p> <p>Doors to be inset and cabinet edge to be wrapped with nosing trim.</p> <p>Note: Non-Torque Hinges on all ALS Cabinet Doors.</p> <p>(1) Adjustable Shelf PN: 64-113780 located in middle ALS Cabinet area.</p> <p>NOTE: GEN-T 171 Models Only</p>	330
99-0329	<p>Assist Bar: Bennington Bar mounted floor to ceiling at head of squad bench with upholstered, padded cushion installed on both sides. (PN: 49-10-1613)</p> <p>NOTE: For RP90/PC90/Sprinter Type III Only/Gen-T to fabricate pads</p>	673
99-0856	Assist Rail: SHORTENED, 48" x 1.25" Stainless Steel" with radius ends, over primary patient. ILOS	33
800057	Assist Rail: 1.25" Stainless w/Radius Ends, Over Squad Bench- IATS	165
99-0761Y	Assist Rail: 1.25" x 48", Powder coated "Safety Yellow", stainless with radius ends, IATS	132
99-0760Y	Assist Rail: 1.25" x 48", Powder coated "Safety Yellow", stainless with radius ends, ILOS	66
99-0761SS	Assist Rail: 1.25"x 48", stainless with radius ends, over squad bench IATS	132
99-0760SS	Assist Rail: 1.25"x 48", stainless with radius ends, over squad bench ILOS	66
99-0613-B	Assist Rail: 72" Powder Coated Blue SS 1.25" with Radius Ends, ILOS -All Models	66
99-0615-R	Assist Rail: 72" Powder Coated Rebel Red SS 1.25" with Radius Ends, IATS -All Models	198
99-0613-R	Assist Rail: 72" Powder Coated Rebel Red SS 1.25" with Radius Ends, ILOS -All Models	66
99-0615-Y	Assist Rail: 72" Powder Coated Safety Yellow SS 1.25" with Radius Ends, IATS -All Models	145
99-0613-Y	Assist Rail: 72" Powder Coated Safety Yellow SS 1.25" with Radius Ends, ILOS -All Models	66
99-0855	Assist Rail: SHORTENED, 48" x 1.25" stainless with radius ends, over squad bench IATS	132
99-2423	<p>Main Cabinet Wall: Cabinet Layout B, Reconfigure Streetside Cabinet Wall to remove the AFT angled cabinet over the CPR seat and extend the upper rear main cabinet to the aft edge of the CPR Seating area. Cabinet will have full length sliding polycarbonate doors facing the aisle.</p> <p>NOTE: Gen-T Only</p>	300
99-2426	<p>Main Cabinet Wall: Install forward facing cabinet on the left rear wall of the 2nd action area facing the CPR seat. This cabinet will be 12" deep x 18" wide x as tall as possible and will have 3 adjustable interior shelves within this cabinet. There shall be a pair of inset acrylic doors with a pair on Eberhard pinch latches to secure the doors.</p> <p>NOTE: Gen-T Only</p>	550
99-2427	<p>Sharps/waste: A sharps and waste space (sized for a Becton-Dickinson 8.2 Qt. sharps container and a 7 Qt. waste) shall be located at the aft end of main countertop and accessible thru a drop in acrylic door.</p> <p>Additionally, have a side hinged surface mount red aluminum door with handle on the outside of the offset located in the #2 compartment, for the purpose of removing the containers for the exterior of the vehicle.</p>	660
99-0941	<p>Cabinet: (2) Acrylic Doors with (2) non-locking, round Southco stainless steel latches Installed on each door below 2nd A/A Shelf, ILO the tilt-out waste/sharps storage cabinet.</p> <p>NOTE: Gen-T ONLY</p>	231
99-1144	Cabinet: Add recessed pocket below A/A countertop for SSCOR suction canister and Vacuum outlet ILO mounting canister on the A/A panel.	330
99-1155	<p>Cabinet: Below main Action Area shelf. Will extend forward of (2) airway drawers to forward edge of exterior compartment #2. Cabinet will have double sliding polycarbonate doors. Cabinet recesses into exterior compartment #2 and requires custom exterior tub.</p> <p>NOTE: Gen-T Type I ONLY</p>	594
99-0956	<p>Cabinet: Curbside work station with Corian counter top and (2) aluminum drawers, with HD slides - stacked below the curbside work station countertop. Both will have LifeDefender non-locking latches. Drawers will face curbside tech seat over wheel well and top drawer will have a hinged polycarbonate lid to be used as an optional writing surface.</p> <p>Top drawer to have approximate inside dimensions: 15.5"W x 2.5"H x 15"D (PN: #: 33-105828).</p> <p>Bottom drawer to have approximate inside dimensions: 15.5"W x 3.5"H x 17"D (PN: #: 33-105338)</p> <p>NOTE: DO NOT ORDER STANDARD S.S. INTERIOR TRIM AT SIDE ENTRY DOOR, ORDER FROM PRINT: 33-103282.</p> <p>NOTE: Gen-T 171 Type III ONLY</p>	1056

99-1111	Cabinet: Curbside work station with Corian countertop and (2) Powder Coated aluminum drawers, with HD slides - both below the curbside work station Corian countertop. The top drawer to pull out towards side seat and have inside dimensions: 15.5"W x 3"H x 15"D with a hinged polycarbonate lid. The bottom drawer to pull-out towards the aisle will be below the top drawer. Both drawers will have a non-locking LifeDefender latch. See Assembly print: 43-A12009 Rev B. This cabinet will be attached to the curbside wall (with backer plates) and brace below. Bottom Drawer: 33-103697 with 63-04-3110/3111 slides and Top Drawer: 33-103698 with 63-04-3100 slides. NOTE: Gen-T 171 Models ONLY	1023
99-1071	Cabinet: Custom Main SS rear wall, 2nd action area to be 22.125"W x 18.875"H (requires offset in exterior compartment #3). Cabinet to have standard CPR seat, standard tip-out sharps/waste aft of the CPR seat and the recessed suction.	726
99-0825	Cabinet: Custom Main SS rear wall, 2nd action area to be 22.125"W x 18.875"H (requires offset in exterior compartment #3). Cabinet to have standard CPR seat, standard tip-out sharps/waste with drawer installed above the tip out cabinet which will raise the 2nd action area counter top and reduce the height of Cabinet "A".	990
99-0753	Cabinet: Drawer, (1) Aluminum pull-out drawer with HD Keyline slides - below the Action Area countertop with inside dimensions: 10.25"W x 3"H x 17"D (PN: 33-102898). Will have a LifeDefender latch. Requires offset in compartment #2 tub (PN: 33-10-2894). NOTE: Gen-T 171 Type III Models ONLY	693
99-0895	Cabinet: Drawers, (2) Aluminum pull-out drawers with HD slides - stacked below the rear Action Area with inside dimensions: 10"W x 3.5"H x 17"D (PN: 33-10-4892). Both will have a non-locking LifeDefender latch on the drawer face. ILOS tip out waste/sharps storage. NOTE: Gen-T 171 Type III Models ONLY	568
99-1790	Cabinet: Inside/Outside Access to Compartment #6: With single 1/2" Acrylic hinged door and Eberhard two-point pinch latches - for Gen-T II only Locate: On LH side of Compartment #6 interior cabinet wall for access to shelves in Compartment #6	363
99-0874 T1	Cabinet: Rear Overhead, (2) 11ga steel, black powder-coated glove box doors PN:33-102030, (1) each side of center mounted clock, ILOS. Rear overhead cabinet drawing: CNC 43-10-3705 NOTE: Gen-T 171/158 Type I ONLY	231
99-0874 T3	Cabinet: Rear Overhead, (2) 11ga steel, black powder-coated glove box doors PN:33-102030, (1) each side of center mounted clock, ILOS. Rear overhead cabinet drawing: CNC 43-10-3705 NOTE: Gen-T 171/158 Type III ONLY	231
99-0105	Cabinet: Squad Bench Overhead for 154, with (2) flip-up 1/2" Acrylic doors, (2) 2" round Southco stainless steel latches on each door and full length stainless steel piano hinge at top.	726
99-1164	Cabinets: Drawers, (1) Aluminum pull-out with HD Keyline slides - (interior dims: 10.5"W x 3.5"H usable height x 17"D) with (1) non-locking, 2" round Southco stainless steel latch on drawer face. LOCATION: Below main Action Area countertop - this will cause an offset in compartment #2. See special tub in compartment section.	462
99-1773	Cabinets: Drawers, (1) ALUMINUM pull-out with HD Keyline slides and LifeDefender latch on drawer face - sized to fit a Smithworks IV warmer (inside dimensions of drawer: 19"W x 15"D x 3.5"H) (dealer will supply and install Smithworks) - drawer to have curly cord connected from back wall of drawer to back wall of inside drawer cabinet - see option 99-0854 in the Electrical Section for wiring through relay. (Cabinet design to allow for the excess room needed behind the drawer for the curly cord to move); ORDER FROM PRINT: 33-103793. Locate: Below the 2nd Action Area on an M2, above the waste tilt-out. This will cause the 2nd action area countertop to raise up and thus decreasing height of cabinet "A" and "C". NOTE: Gen-T Models ONLY	660
99-0859	Cabinets: Drawers, (1) Aluminum pull-out with HD slides and Southco stainless steel non-locking latch on drawer face - sized to fit a Smithworks IV warmer (inside dimensions of drawer: 19"W x 12"D x 5.375"H) (dealer will supply and install Smithworks) - drawer to have curly cord connected from back wall of drawer to back wall of inside drawer cabinet - see option 99-0854 in the Electrical Section for wiring through relay. (Cabinet design to allow for the excess room needed behind the drawer for the curly cord to move)	660
99-1774	Cabinets: Drawers, (2) ALUMINUM build pull-out with HD Keyline slides - stacked below the Action Area countertop with inside dimensions: 10"W x 3"H x 17"D. Both will have non-locking LifeDefender latches. Requires offset in compartment #2 tub PN: . Note: drawers to be aluminum build - see print 33-103729)	858

99-0896	Cabinets: Drawers, (2) Aluminum pull-out drawers with HD slides - stacked below the Action Area countertop with inside dimensions: 10"W x 3.5"H x 17"D (PN: 33-10-3729-Rev A). Both will have (1) non-locking, 2" round Southco stainless steel latch on each drawer face. Requires offset in compartment #2 tub (PN: 33-10-2894). NOTE: Gen-T 171 Type III Models ONLY	832
99-0842	Cabinets: Forward Action Area, recessed into A.A. wall. Cabinet to be full height of Action Area, 4.375" Deep and 12" wide with 1- fixed shelf at mid point, single 1/2" Acrylic door hinged on right hand side with (2) non-locking, 2" round Southco stainless steel latches. See Print 43-A11109 Rev A. The A.A. overhead cabinet will require special print for Action Area panel.	389
99-1425	Cabinets: Interior Access above 1/2 Compartment #3 with sliding 3/16" polycarbonate doors ILOS hinged dual Acrylic doors inside/outside access to compartment #3. Cabinet to have one adjustable shelf. NOTE: Gen-T / GT-167 Models ONLY	330
99-1778	Cabinets: Interior Access above 1/2 Compartment #3. Cabinet to have dual 1/2" Acrylic, hinged doors with (1) non-locking Eberhard two-point pinch latches on each door, (1) adjustable shelf. NOTE: Gen-T Models ONLY	594
99-0438	Cabinets: Interior Access above 1/2 Compartment #3. Cabinet to have dual 1/2" Acrylic, hinged doors with (2) non-locking, 2" round Southco stainless steel latches on each door, (1) adjustable shelf.	495
99-0826	Cabinets: Interior Access at Compartment #3 offset - 8" deep custom cabinet to have dual 3/16" sliding polycarbonate doors with full length extruded handles, (1) adjustable shelf	376
99-1796	Cabinets: Interior Access at Compartment #3 offset - 8" deep custom cabinet to have dual, hinged 1/2" acrylic doors with (1) Eberhard two-point pinch latch on each door and (1) adjustable shelf.	389
99-2568	Cabinet: Additional over foot end of squad bench that protrudes into the #6 Compartment. Cabinet will be 24"H x 12"W x 10"D. Cabinet will face the squad bench and have a side hinged LifeDefender acrylic door with a non-locking LifeDefender latch. There shall be (2) adjustable interior shelves w/lips inside this cabinet that have rubber matting. Acrylic door to be inset with nosing trim, and attached with non-torque hinges. There will be Three (3) powder coated, aluminum drawers below this cabinet with non-locking LifeDefender latches. Each drawer to be 12" wide x 10"D x 4"H exterior dimensions. Requires separate compartment #6 option, see body section. Note: Gen-T 171 only.	3120
99-2549	Cabinet: Gen-T 171 model, Rear of Squad Bench. Install an insert cabinet at the rear of squad bench protruding into the #6 Compartment up to the divider. Cabinet bottom to start at 45" above the exterior compartment floor. Cabinet will have 30"H x 14"W x 10"D inside dimensions. Cabinet will face the squad bench and have a pair of side hinged inset acrylic doors with locking defender latches. There shall be (3) adjustable interior shelves w/lips inside this cabinet. Shelves to have interior rubber matting. On the exterior of this insert cabinet, install a single right hinged acrylic inset door to gain access to the shelving from the #6 compartment. NOTE: THIS OPTION INCLUDES THE SPECIAL COMPARTMENT #6 WITH CUTOUT FOR INSERT CABINET. ORDER TUB FROM PRINT #77-113775, WILL REQUIRE RUBBER COATED TRIM TO BE INSTALLED AROUND CUT-OUT AND INSERT CABINET.	1890
99-1009	Cabinets: Rear Overhead cabinet over rear door opening split into (2) cabinets w/ a single flip-up 1/2" Acrylic door w/(2) round SouthCo latches and Austin constant torque hinges over each opening ILOS one large opening, single door and stainless steel hinges. NOTE: Gen-T models only.	330
99-1065	Cabinets: Rear Overhead, Cabinet over rear door opening with (1) flip-up 1/2" Acrylic door with (2) non-locking, 2" round Southco stainless steel latches. - This storage is narrowed for radio speaker install on each side of opening. ILOS See narrowed Acrylic door print PN: 52-10-5615 and cabinet face PN: 43-A11464	231
99-1509	Cabinets: Rear Overhead, Cabinet to have Austin constant torque hinges installed, ILOS stainless steel hinges.	92
99-2751	Cabinet: Rear Overhead with (2) "INSET" flip-up 1/2" Acrylic doors. There shall be (2) Austin constant torque hinges and (1) Defender latch on each door. There shall be one door located on each side of a center mounted clock, ILOS. Install clock on center of cabinet in between the two storage cabinet sections. Requires adding in a separate clock option, see electrical section. Note: Gen-T 171 only.	175

99-2328	Cabinet: Rear Overhead, (2) 11ga steel, black powder-coated glove box doors PN:33-102030, (1) each side of center mounted clock, ILOS. Rear overhead cabinet to be powder coated aluminum. Note: For Gen-T Only.	240
99-2523	Cabinet: Drawer, (1) Aluminum build pull-out w/HD slides below 2nd Action Area ILOS cabinet. Inside dimensions to be: 16"W x 6"H x 17"D. Install a locking defender latch on the front of the drawer. Note: Gen-T 171 only.	480
99-2407	Cabinet: Drawers, (1) ALUMINUM build pull-out w/HD slides - stacked below the Action Area countertop w/inside dimensions: 12"W x 4"H x 17"D. with Austin/Defender latch. Requires offset in compartment #2 tub PN:XX- NOTE: GEN-T models only.	630
800070	Cargo Net: Head of squad bench- Type II Chevy ONLY	277
99-0546	Cargo Net: Head of Squad Bench- Type I / III (167, RP-90, Gen-T II) PN: 63-08-0022, bolted to taping plates in the floor, wall and ceiling. PN: ZRS-NETMEX009-02-A.	376
99-0511	Cargo Net: Head of squad bench- Type I / III 154 Models. Squad Bench to accommodate mounting plate and cover secured to wall structure. (150 PNs: 63-08-0021, 33-101868, 33-101869) Requires squad bench assembly print different than standard	576
800090	Corian Countertop- 1st / 2nd Action Area, Color: _____ w/ _____ Top and perimeter accent lips. To extend over the edge of cabinet main	1254
99-0975	CPR Seat: Extend a 3/4" dividing wall from the action area overhead down to the countertop to close off the access to the countertop from the CPR seat. Add a full Pad to cover this wall.	99
99-0940	CPR Seat: Install gas strut hold open on lid to meet State of Massachusetts regulations	66
99-0782	Defibrillator Mount: Ferno P-300 Defibrillator Mount Kit for Philips HeartStart MRx. Requires 0.25"x15"x15" mounting plate installed beneath the countertop. Must use a Corian spacer beneath the mounting base so monitor swivels above the countertop lip.	1155
99-0851	Defibrillator Mount: NCE H7000 LifePak 12/15 Interchangeable monitor mount installed on rear action area shelf with aluminum backer plate PN:33-10-3043 and Corian spacer for swivel base.	1122
99-0851-A	Defibrillator Mount: NCE H7000A LifePak 12/ Interchangeable monitor mount installed on rear action area shelf with aluminum backer plate PN:33-10-3043 and Corian spacer for swivel base.	1181
99-1033	Defibrillator Mount: Phillips MRx Shelf Defibrillator Mount Kit with Swivel; NCE Part# H8000A, Requires 0.25"x15"x15" mounting plate installed beneath the countertop. Must use a Corian spacer beneath the mounting base so monitor swivels above the countertop lip. Must Specify Location:	1155
99-0827	Defibrillator Mount: Zoll X9000 LifePak monitor mount installed on rear action area shelf with aluminum backer plate PN:33-10-3043 and Corian spacer for swivel base.	1056
800190	Drug Box: Metal box with locking door mounted inside cabinet, see print 33-10-2124 Must Specify Location:	317
99-0982	File/Map Hanger Storage: Formed aluminum with (3) file pockets stacked vertically. Will be white powder coated. Install on cab side of bulkhead below the Pass-Thru window, centered. See print #33-102689.	330
99-0679	Glove Box Holder: Aluminum, powder coated white, 3-Hole Glove Box Holder with Positron hinged, slotted lid mounted on bulkhead between cab seats on Type III pass through wall. Glove boxes will store vertically, side by side. Lid has three oval cut-outs, oriented the same way. MX01533. See print 33-102403. Locate up high below Pass-Through. Make sure flip-up lid will open and not interfere with armrests on passenger and driver seats.	257
99-2430	Glove Box Holders: (2), stacked, w/single hinged, black 11ga steel powder-coated door recessed into compartment #6 over foot end of bench. (Requires special tub, see option in body section) NOTE: GEN-T ONLY	275
800170-3	Glove Box Holders: (3) w/hinged, black 11ga steel powder-coated door, in cabinet above rear entry door	231
99-0798	Glove Box Holders: (3) with hinged, black 11ga steel powder-coated door, above Curbside Entry Door	231
800170-4	Glove Box Holders: (4) w/hinged, black 11ga steel powder-coated door, in cabinet above rear entry door	233
99-1109	Glove Box Holders: Boundtree #290001, white, baked enamel- 5.5" x 10" x 3.75". Specify Location(s): Bulkhead wall above center floor console-cab side, side by side. (mounted vertically)	112
99-0923	Grab Handle: (1) 12" x 1.25" Powder Coated Safety Yellow IATS -	125
99-0745-B	Grab Handle: (1) 18", Powder Coated Blue, 1.25" SS with Radius Ends PN: G304-49101356PCBY, IATS Location:	132

99-0745-R	Grab Handle: (1) 18", Powder Coated Rebel Red, 1.25" SS with Radius Ends PN: G304-49101356PCBR, IATS Location:	152
99-0745-Y	Grab Handle: (1) 18", Powder Coated Safety Yellow, 1.25" SS with Radius Ends PN: G304-49101356PCBY, IATS Location:	132
99-1210	Grab Handle: (1) 36" 1.25"OD 304SS, Offset Grab Handle with Radius Ends PN: G304-49104126, IATS Location:	132
99-1209-R	Grab Handle: (1) 36", Powder Coated Rebel Red, 1.25"OD 304SS, Offset Grab Handle, with Radius Ends PN: G304-49104126PCBR, IATS Location:	165
99-1209-Y	Grab Handle: (1) 36", Powder Coated Safety Yellow, 1.25"OD 304SS, Offset Grab Handle, with Radius Ends PN: G304-49104126PCBY, IATS Location:	165
99-0997	Grab Handle: 1.25" x 12" long Stainless Steel with 30° offset and oval mounting flanges (PN: 49-10-3755). "Not for use with 158 or 171 ALS, or any ALS with doors. Specify handle forward or rearward on door frame of curbside door." Location: Mount on forward side of curbside entry door on the door frame between the door and the ALS cabinet using 1/4" x 20 Type F self tapping machine screws.	132
99-0309	Grab Handle: 18" x 1.25" Stainless steel with radius ends, IATS Location:	73
99-0683-B	Grab Handles: (3) 12", Powder Coated Blue 1.25: SS with Radius Ends- ILOS -All Models	99
99-0683-R	Grab Handles: (3) 12", Powder Coated Rebel Red 1.25: SS with Radius Ends- ILOS -All Models	99
99-0683-Y	Grab Handles: (3) 12", Powder Coated Safety Yellow 1.25: SS with Radius Ends- ILOS -All Models	53
800180	Grab Handles: (3) V-Style Handicapped/Brushed Stainless 1.25 w/Radius Ends- ILOS -All Models	224
99-0614-B	Grab Handles: (3) V-Style, Powder Coated Blue 1.25: SS with Radius Ends- ILOS -All Models	224
99-0614-R	Grab Handles: (3) V-Style, Powder Coated Rebel Red 1.25: SS with Radius Ends- ILOS -All Models	224
99-0614	Grab Handles: (3) V-Style, Powder Coated Safety Yellow 1.25: SS with Radius Ends- ILOS -All Models	224
99-0759	Grab/Assist Handles: Powder Coated Safety Yellow, all overhead, rear main and ALS mounted 1.25: SS handles with radius ends- ILOS - Transit Only	53
99-0946	Inventory Control: 3/4" holes drilled in opposing 3/16" polycarbonate doors for inventory control straps. Drill holes at mid-point on doors at opposite ends from full length extruded handles. (No Footman loops used in this option) Price per cabinet location. Specify Location(s):	20
99-0029	Inventory Control: For sliding polycarbonate cabinet doors- Footman loops and hole drilled in grab handle for wire tie; Price per cabinet location. Specify Location(s):	46
99-0189	IV Pole: 7/8" SS medical equipment / IV Pole, IATS	66
99-0977	Latch: Squad Bench, TriMark, Install (1) flush mount, powder coated black paddle handle in face of squad bench IATS to meet state mandated regulations. Transit Type II Only	165
99-0368	Lock: Cabinet, KabaMas CL-20 (KMCL20SMK5SEWBE1) with key override sensor Kit (KM321103)	700
99-1622	Lock: Codelocks push button Kitlock Model KL1000 cabinet lock. This lock is for 3/4" cabinets. LOCATION: Must Supply	158
99-1784	Lock: CompX Regulator REG-S-L-3 electronic, keyless self-locking with pushbutton access and SlamCAM spring loaded latch Specify Location(s): Must specify	231
99-1839	Lock: LifeDefender CW-LOCKASSY-545 tumbler lock to work with LifeDefender cabinet door or drawer latch. Specify Location(s): Must specify	132
99-0593	Main Cabinet Wall: 2nd Action Area aft of CPR seat on RP-90 Models with 125VAC and 12VDC receptacles. Deletes cabinet A2 aft of CPR seat. NOTE: Includes 33-10-2292 backer plate mounted below shelf for future monitor mount installation.	330
99-0894	Main Cabinet Wall: Extended Action Area with 2nd full depth Overhead cabinet with (1) adjustable shelf. Extended action area to provide 20" clearance above A/A shelf for Monitor Mounting. Upper and Lower Rear Cabinets to extend from end of 2nd action area as far to the rear as physically possible.	396

99-1108	Main Cabinet Wall: Reconfigure street side cabinet wall to eliminate the two (2) angled cabinets fore and aft of the 26.5" W CPR Seat. Make the 2nd Action Area 22"W x 21.875"H, this will narrow the storage to the rear of the 2nd Action Area and decrease the height of the upper rear cabinet. Narrow the Action Area Overhead and Action Area Counter top to allow the CPR seat to shift towards the front of the module. Square off Action Area Overhead and Upper Rear Main cabinet at CPR seat. The Upper Rear Main cabinet will be flush with the plane of the Street side cabinet wall.	990
99-0992	Main Cabinet Wall: Reconfigure Streetside Cabinet Wall to delete the standard (2) angled cabinets on either side of CPR Seat. 2nd Action Area to be 22" W x 19.375" H, this will reduce the width of the rear inside cabinet over 1/2 height compartment #3.	330
99-1158	Main Cabinet Wall: Reconfigure Streetside Cabinet Wall to delete the standard (2) angled cabinets on either side of CPR Seat. 2nd Action Area to be 50" W x 20.875" H. 2nd A/A counter top to be Corian full width. Upper rear cabinet to be flush with lower main.	1320
99-1072	Main Cabinet Wall: Reconfigure Streetside Cabinet Wall to eliminate the two (2) angled cabinets fore and aft of the CPR seat. The 2nd action area will be 17.625"w x 21.875"h. The CPR seat will be widened to 32" shifting forward and eliminating the recessed suction. This will reduce forward action area countertop and overhead cabinet. The overhead cabinet fore and aft of the CPR seat will be squared off eliminating the angled cabinets. The upper rear cabinet will be flush with the face of the streetside cabinet wall. Note: do not order standard seat pad, it is wider now.	660
99-0540a	Main Cabinet Wall: Restocking Feature, Interior Cabinet, Over 40" Width- Sliding Acrylic door with hinged, keyed frame with (2) Titan 20-pound gas struts and (2) spring-loaded elbow catches. Location: Must Specify exact cabinet locations.	330
99-0540	Main Cabinet Wall: Restocking Feature, Interior Cabinet, Under 40" Width- Sliding Acrylic door with hinged, keyed frame with (2) Titan 15-pound gas struts and (2) spring-loaded elbow catches. Location: Must Specify exact cabinet locations.	330
99-0939	Main Wall: Reconfigure Streetside Cabinet Wall to delete the standard (2) angled cabinets on either side of CPR Seat. 2nd Action Area to be 22" W x 21.875" H, this will cause the 2nd A/A to protrude into compt. #3 (special tub). Upper rear cabinet face to be flush with Lower Main. Includes Engineering time. NOTE: Gen-T Models Only	660
800250	Riser: Stainless steel on squad bench face (Standard on Gen-T)	330
800260	Riser: stainless steel on streetside lower main (Standard on Gen-T)	330
99-0411	Seating: EVS Seat Base, EVS CBDL with latching Door- ILOS	99
800140	Seating: EVS Swivel Base SB-2 two position swivel base for EVS Child seat, ILOS cabinet base	235
99-0828	Seating: EVS Technician's Seat 1860V4B child attendant flip seat with V-4 seat belt system, ILOS on "Transit Only".	627
99-1058	Seating: EVS Technician's Seat 1880 with 10 ⁹ back Child Restraint System, Rear facing automotive style chair with 4Pt seat belt system mounted on standard steel base- ILOS 4Pt seat.	396
99-0914	Seating: EVS Technician's Seat 1880 with Child Restraint System, Rear facing automotive style chair with 4Pt seat belt mounted on Heater Steel Base- ILOS 4Pt seat and base.	462
99-0393-R	Seating: EVS Technician's Seat 1900RV4B Executive, Reclining Captain's Chair with V4 Seat Belt, ILOS EVS 1780 with V4 belt system.	937
99-0393	Seating: EVS Technician's Seat 1900V4B Executive Captain's Chair with V4 Seat Belt, ILOS EVS 1780 with V4 belt system.	759
99-0993	Seating: EVS Technician's Seat 2000RV40 Executive Captain's Chair with V4 Seat Belt and recline feature, ILOS EVS 1780 with 4 point belt	660
99-1061	Seating: EVS Technician's Seat Arm Rest for 1760, 1780, 1780E, 1850, 1860, 1880 seats. Must be ordered with seat.	231
99-1044	Seating: EVS Technician's Seat Arm Rest for 1900/2000 seats, Must be ordered with seat.	275
99-0720	Shelf: Adjustable Acrylic, in interior cabinet IATS where there is an existing shelf.	92
99-0721	Shelf: Adjustable Acrylic, in interior cabinet IATS where there is no existing shelf.	125
99-0863	Shelf: Liner, (1) pliable, skid resistant rubber shelf liner installed on individual interior shelf. Gindor Black Pebble Grain matting to be installed on interior cabinet shelf as specified. Location: Must Specify	59
800235	SouthCo Latches, Round, Metal, Locking- IATS each NOTE: Non-Storage or Content Less than 5lbs.	66
800230	SouthCo Latches, Round, Metal, Locking- ILOS each NOTE: Non-Storage or Content Less than 5lbs.	51

800245	SouthCo Latches, Round, Metal, Non-Locking- IATS each NOTE: Non-Storage or Content Less than 5lbs.	66
800240	SouthCo Latches, Round, Metal, Non-Locking- ILOS each NOTE: Non-Storage or Content Less than 5lbs.	51
99-1070	<p>Squad Bench: TRANSIT ONLY - EVS 1760 seat (order seat with swivel base mounted in right hand position) with Four point harness (without EVS base) mounted on aluminum framed platform over wheelwell built in house-see print #35-A13127. Seat to swivel and lock in side and forward positions. Base to have HDPE enclosure, see print # 46-A13128.</p> <p>Order steel wall frame from print #35-A11683 & Fiberglass wall print for side seat configuration #46-102569.</p> <p>**NOTE: THIS SIDE SEAT TO BE POSITIONED TOWARDS THE REAR AS MUCH AS POSSIBLE - REFERENCE LAST TRUCK 18-TRVG0534.**</p> <p>Cabinet on CS rear behind side seat for Reeves Sleeve and splints etc. Will be HDPE and have a solid door, hinged on left side with Life Defender Latch . Door opens towards aisle, order from print # 52-102775 Rev E. Wall pad print 86-102770, side trim pad print 86-104316, S.S. trim pieces: 33-102974, 33-102973 & steel backer plate: 33-102964.</p> <p>Install HDPE cabinet with laptop platform, tilt-out sharps/waste and Life Defender latch in front of curbside seat (when in forward facing position). Countertop surface on top will be HDPE for a flat writing surface (all one piece with cabinet), see print # 52-102774 Rev C.</p> <p>Sharps/Waste: Tilt out to drop in, located on aisle side of HDPE cabinet forward of curb side tech seat, order bracket from print: #33-100847.</p>	3960
99-0086	Straps: (3) 1" webbed material w/plastic buckle for Type II ALS cabinet shelves.	66
99-2271	Threshold Trim: Stainless steel threshold trim package for GT-154 modular entry and compartment doors. NOTE: GT-154 Only	330
99-0483	Threshold Trim: Stainless steel threshold trim package for GT-167 modular entry and compartment doors. NOTE: ME-167 Only	330
800280	Walk-Thru DELETE: Pass-Thru window ILOS on Type III or Type II - includes horizontal sliding Lexan window mounted on the cab side with full length extruded/anodize aluminum handle to facilitate access.	99
900057	Cot Mount: Ferno #175-4 ILOS Ferno #175-3 Mounting Locations:	264
99-0729	Cot Mount: Ferno 175-3, Removable floor mounted cot mount. Models: RP-90ES, RP-90MR, PC-90 Mounting Location:	0
99-0730	Cot Mount: Ferno 175-4 Dual Position, Removable Models 154, 158, 167 & 171 Only.	0
99-0723	Cot Mount: Ferno 86" Stat Trac installed in center position, 154" modules only	1914
99-1020	Cot Mount: Ferno 86" Stat Trac System with integrated charging system. GT-154 modules ONLY. Mounting Location:	4686
99-0722	Cot Mount: Ferno 86" Stat Trac System: RP-90, PC-90, DB-147 modules ONLY. Mounting Location:	2112
99-1019	Cot Mount: Ferno 86" Stat Trac with integrated charging system installed in center position, 142" and 146" modules only	4818
99-1021	Cot Mount: Ferno 91" Stat Trac System w/integrated charging system. Transit ONLY, installed in standard position. Install Nylon runner on main wall and order special rear threshold, see print: 33-10-4720. NOTE: For AL Model Only.	5544
99-1154	Cot Mount: Ferno 91" Stat Trac System with integrated charging system. Transit ONLY, installed in standard position. Install Nylon runner on main wall and order special rear threshold, see print: 33-10-3605. NOTE: For SS and TWGK Model Only.	5544
99-2165	Cot Mount: Ferno 91" Stat Trac without ICS installed in Transit models only, installed in standard position. Install Nylon runner on main wall and order special rear threshold, see print: 33-10-3605. NOTE: For SS and TWGK Models Only.	2218

99-1196	Cot Mount: Ferno 91" Stat Trac without ICS installed in Transit models only, installed in standard position. Install Nylon runner on main wall and order special rear threshold, see print: 33-10-4720. NOTE: For AL Model Only.	2218
99-0724	Cot Mount: Ferno 96" Stat Trac System: GT-154 & 167"/Gen-T 158 & 171" models ONLY. Mounting Location:	2310
99-0757	Cot Mount: Ferno 96" Stat Trac with Integrated Charging System installed in center position, 167"/171" modules only	5247
99-0787	Cot Mount: Ferno 96" Stat Trac with Integrated Charging System, install customer supplied Stat Trac with ICS System	396
99-2173	Cot Mount: Ferno InLine Fastener system with Universal Floor mount (with integrated charging system). For GT-154, GT-167, Gen-T 158 and 171 models only ILOS. NOTE: Dealer Must Specify Mounting Location	8646
99-2175	Cot Mount: Ferno ProF1 Universal Cot Fastener system with Universal Floor mount ("NO" integrated charging system). For GT-154, GT-167, Gen-T 158 and 171 models only ILOS. NOTE: Dealer Must Specify Mounting Location	4290
99-2174	Cot Mount: Ferno ProF1 Universal Cot Fastener system with Universal Floor mount (with integrated charging system). For GT-154, GT-167, Gen-T 158 and 171 models only ILOS. NOTE: Dealer Must Specify Mounting Location	6930
99-0728	Cot Mount: Install Customer supplied Stryker Power Load or Performance Load systems, ILOS. NOTE: Includes wiring for charging system when included with system. Mounting Location:	396
99-0725	Cot Mount: Stryker - Power/Performance Load "floor plate only" for RP90, PC90, BL90 models ONLY. Mounting Location:	990
99-0696	Cot Mount: Stryker 6371 Wall-Mount- ILOS Ferno 175-5 Wall-Mount for Transit and Sprinter II	132
900065	Cot Mount: Stryker 6377, Dual Position, Removable Mounting Locations:	264
99-1243	Cot Mount: Stryker large "LOCKING ARM" mounting plate. Mount Stryker Large floor mounting plate for ship loose standard cot mount hardware assembly when installed with customer supplied Power or Performance Load system. Mounting instructions: 12.63" center line to center line from the Stryker floor rail toward the streetside main wall and 28.82" from the rear most end of the Stryker rail to the center of the forward pilot hole for the locking arm. SEE Stryker instructions for clarification.	132
99-0880	Cot Mount: Stryker Performance Load (6392-000-001) with inductive charger and floor plate ILOS 175-3. NOTE: Dealer Must Specify Mounting Location	8283
99-0878	Cot Mount: Stryker Performance Load (6392-000-001) with inductive charger and floor plate ILOS 175-4. NOTE: Dealer Must Specify Mounting Location	8151
99-0882	Cot Mount: Stryker Performance Load (6392-000-001) with inductive charger and floor plate ILOS 175-5. NOTE: Type II and Transit Only NOTE: Dealer Must Specify Mounting Location	8415
99-0881	Cot Mount: Stryker Performance Load (6392-000-002) with floor plate ILOS 175-3. NOTE: RP-90, BL Models Only NOTE: Dealer Must Specify Mounting Location	4983
99-0879	Cot Mount: Stryker Performance Load (6392-000-002) with floor plate ILOS 175-4. NOTE: 154, 167 and Gen-T Models Only NOTE: Dealer Must Specify Mounting Location	4983
99-0883	Cot Mount: Stryker Performance Load (6392-000-002) with floor plate ILOS 175-5 Transit Only. NOTE: Dealer Must Specify Mounting Location	5247
99-2145	Cot Mount: Stryker Power Load Floor mount "Plate Only", GT-154,GT-167, Gen-T 158 and 171. IATS NOTE: Install large floor plate for locking arm from standard cot mounting kit and ship remainder of materials loose. NOTE: Dealer Must Specify Mounting Location	1518
99-1086	Cot Mount: Stryker Power Load System installed in center position, ILOS RP-90ES, RP-90MR, PC-90 and BL Modular Conversions Only. NOTE: Dealer Must Specify Mounting Location	32340
99-1087	Cot Mount: Stryker Power Load System installed in street side wall position only, ILOS Type 2 Conversions Only	32670

99-1088	Cot Mount: Stryker Power Load System with mass casualty fastener (floor plate for rail clamp option). Modular Conversion ONLY Mounting Location Power Load floor Plate: Mounting Location rail clamp floor plate: 12 5/8" from center line of Power Load floor plate to center line of rail clamp floor plate toward the streetside main wall.	33066
99-0726	Cot Mount: Stryker Power/Performance Load Floor mount "Plate Only", GT-154, GT-167, Gen-T 158 and 171 models only. NOTE: Dealer Must Specify Mounting Location	891
99-2011	Cot Mount: Stryker Power/Performance Load floor mount plate assembly kit "Only" installed in standard position, Transit models only.	891
99-1742	Cot Mount: Stryker, Power Load System installed in center position, ILOS GT-154, ME-167, Gen-T 158 and 171 Modular Conversions Only.	32340
900060	Cot Mount: Styker 6370 single position, removable cot mount ILOS FW #175-3, RP90, PC90, BL90 models only. Mounting Locations:	264
900075	Cot Safety Hook: Install at rear threshold Specify Stryker or Ferno:	99
900010	Cot Wheel Plates: Stainless Steel Specify Cot Model:	145
900080	Equipment Pole: 7/8" Stainless Steel with mounting stanchions - IATS Specify Location(s):	99
99-0491	Fire Extinguisher Bracket: Approved Safety& Security, black steel with cam-over lever latch & mounting plate, PN: 63-04-6015, 08-0013.	119
99-0231	Fire Extinguisher: 10lb, ABC with automotive bracket, IATS	145
99-0232	Fire Extinguisher: 10lb, ABC with HD automotive style bracket, ILOS	86
900070	Floor Plates: Additional for Ferno #175-4 Cot Mount Specify Cot Model:	275
900100	Wheel & Post Cups: Install for Ferno # 107 Stair Chair	119
900110	Wheel & Post Cups: Install for Ferno # 11 Stretcher	119
99-0795	Entry Doors: Lower Kick Panels, smooth aluminum with reflective chevron installed ILOS ADP. NOTE: Must Specify Colors	231
1000090	Paint: Roof of Module to be different color that rest of Body from lower edge of roof radius up and over around the entire perimeter of the roof. Color: Color Code: Configuration: NOTE: Requires Approved Drawings Prior to submitting order. Paint spray samples must be approved prior to scheduling.	1056
1000010	Paint: Beltline Stripe with Hockey Stick Stripe Color: Color Code: Configuration:	1452
1000050	Paint: Beltline Stripe with QRS Pattern Color: Color Code: Configuration:	1848
1000060	Paint: Beltline Stripe Color: Color Code: Configuration:	1188
1000080	Paint: Body Only, Custom Color to Match Chassis Color: Color Code: Configuration: NOTE: Requires Paint Color and Code Prior to submitting order. Paint spray samples must be approved prior to scheduling.	1320

1000072	Paint: Mid-Body Down Type 1 Color: Color Code: Configuration: NOTE: Requires Approved Drawings Prior to submitting order. Paint spray samples must be approved prior to scheduling.	3960
1000070	Paint: Mid-Body Down Type 3 Color: Color Code: Configuration: NOTE: Requires Approved Drawings Prior to submitting order. Paint spray samples must be approved prior to scheduling.	2640
1000020	Paint: Skirt line Stripe Color: Color Code: Configuration:	1056
1000086	Paint: Type 1, Body and Chassis, Custom (2) Color Scheme Color: Color Code: Configuration: NOTE: Requires Approved Drawings Prior to submitting order. Paint spray samples must be approved prior to scheduling.	10560
1000082	Paint: Type 1, Body and Chassis, Custom Color Color: Color Code: Configuration: NOTE: Requires Paint Color and Code Prior to submitting order. Paint spray samples must be approved prior to scheduling.	9240
1000088	Paint: Type 3, Body and Chassis, Custom (2) Color Scheme Color: Color Code: Configuration: NOTE: Requires Approved Drawings Prior to submitting order. Paint spray samples must be approved prior to scheduling.	7920
1000084	Paint: Type 3, Body and Chassis, Custom Color Color: Color Code: Configuration: NOTE: Requires Paint Color and Code Prior to submitting order. Paint spray samples must be approved prior to scheduling.	6600
1000105	Star-of-Life Package, SHIP LOOSE	165
1000145	Vinyl Graphics: Chevrons, 2-Color: Full Rear, 6" Diamond Grade Reflective Stripes Color #1: Color #2:	1980
1000130	Vinyl Graphics: Chevrons, 2-Color: Rear Excluding Doors, 6" Standard Grade Reflective Stripes Color #1: Color #2:	1122
1000065	Vinyl: Beltline Stripe, 10" Reflective Color:	1056
1000140	Vinyl: Chevrons, 2-Color: Full Rear, 6" Standard Grade Reflective Stripes Color #1: Color #2:	1584
1000155	Vinyl: Chevrons, 2-Color: Full Rear, 6" Stripe WRAP Color #1: Color #2:	1254

1000135	Vinyl: Chevrons, 2-Color: Rear Excluding Doors, 6" Diamond Grade Reflective Stripes Color #1: Color #2:	1386
1000150	Vinyl: Chevrons, 2-Color: Rear Excluding Doors, 6" Stripe WRAP Color #1: Color #2:	924
1000040	Vinyl: Pinstripe, 1/4" Reflective on both edges of Beltline Color:	231
1000025	Vinyl: Skirt line Stripe, 8" Reflective Color: Color Code: Configuration:	726